



2018 (Version 1)

QINGDAO MARCHER RUBBER CO.,LTD

Add 22F Fulin Mansion No.87 Fuzhou Road,
Qingdao China
Tel :+86 532 85764112
Fax :+86 532 85764260
Web: www.marchertire.com
E-mail: admin@marchertire.com

DISTRIBUTED BY:

VISIT US:



CONTENTS

CONSTRUCTION TIRES.....01-04

OTR TIRES 05-18

AGRICULTURAL TIRES 19-29

SOLID TIRES 30-32

MARCHER INTRODUCTION

Headquartered in Qingdao of China, QINGDAO MARCHER RUBBER CO., LTD (MARCHER) is a leading manufacturer and player in the global Off-Highway tire market.

Since the founding in 1998, MARCHER has achieved the 93,000-square-meter factory consisting of R&D department and over 62,000 square meters for production plant in Qianlou Rubber Industrial Park of Qingdao, China.

Currently, MARCHER annual production capacity is

- ★ 100,000 sets of OTR tires along with 8,000 giant tires and 20,000 radial,
- ★ 400,000 sets of construction and industrial tires, including 10,000 radial,
- ★ 200,000 sets of agricultural tires, comprising 50,000 radial and 10,000 forestry tires,
- ★ 800,000 solid tires.

All tires produced by MARCHER are in full compliance with international manufacturing and management standards & regulations, including ISO9001, US DOT and the national CCC, European Directive REACH, E-MARK, etc. They have successfully been operated in more than 100 countries & regions, and already proved by Rio Tinto & FMG in Australia, and Shenhua Group of China, etc.

With "All-for-Durable" and environmental-friendly design philosophy, MARCHER is offering the most integrated production line, for equipment in agricultural, construction and industrial events as well as earthmoving, port and mining, and gardening applications. Believing in particularity, honesty and friendship, we are always ready to run all over the world.



TIRE ON EQUIPMENT



PRODUCE QUALITY TIRE

RUN ALL OVER THE WORLD

AGRO-INDPRO100 R-4

- Applications: backhoe, telescopic and compact loader.
- The tread pattern enables strong grip and high traction performances on soft surfaces, as well as comfortable work on hard surfaces.
- The steel belted construction contributes to high stability of the machine, especially when working on sloppy terrains, and complete puncture protection.
- Long tread life and low tread wear are due to special tread design and durable tread rubber compound is another feature of this tire.



Size	Load Index	Rim	Type	Inflated Dimensions		Load Capacity		Inflation Pressure		Max Speed		Replacement
				SW (mm)	OD	kg		psi	bar	mph	km/h	
340R018 IND	143A8/143B	11.00	TL	350	1001	6000	2725	58	4.0	25	40	12.5/80R18
340R020 IND	144A8/144B	11.00	TL	343	1052	6160	2800	58	4.0	25	40	12.5/80R20
400R024 IND	161A8/161B	DW13	TL	404	1250	10450	4750	58	4.0	25	40	15.5/80R24
405/70R24 IND	152A8/152B	DW13	TL	402	1177	7820	3550	58	4.0	25	40	16/70R24
440R024 IND	161A8/161B	DW14L	TL	449	1309	10190	4625	58	4.0	25	40	16.9R24
440R028 IND	156A8/156B	DW14L	TL	460	1410	8810	4000	46	3.2	25	40	16.9R28
4456R22.5 IND	175A8/182A2	14.00	TL	452	1192	15180	6900	109	7.5	25	40	18R22.5
460/70R24 IND	159A8/159B	DW15L	TL	462	1250	9625	4375	58	4.0	25	40	17.5LR24
480R026 IND	160A8/160B	DW15	TL	489	1423	9910	4500	46	3.2	25	40	18.4R26

SKS L-2

- Applications: skid steer, aerial boom lift, scissor lift, compact tractor, front backhoe, 3-wheel forklift.
- The ideal tire for loose surfaces and heavy-duty service.
- The extra deep tread and sidewall protection providing excellent cut and chip resistance and outstanding durability.



Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions		Load Capacity (kg)	Inflation Pressure (kPa)
					SW (mm)	OD (mm)	10km/h	10km/h
5.70-12	4	4.50	TL	14.0	146	570	658	415
	8	4.50	TL	14.0	146	570	850	550
23x8.50-12	6	71-55	TL	12.0	213	574	820	340
	10	71-55	TL	12.0	213	574	1020	480
26x12.00-12	6	10.5I-55	TL	13.0	307	648	1110	240
	10	10.5I-55	TL	13.0	307	648	1630	450
	12	10.5I-55	TL	13.0	307	648	1890	550
27x8.50-15	6	7JA	TL	15.0	218	681	1210	315
	8	7JA	TL	15.0	218	681	1310	415
	12	7JA	TL	15.0	218	681	1510	620
27x10.50-15	8	8LB	TL	15.5	259	699	1410	415
	12	8LB	TL	15.5	259	699	1610	620
31x15.50-15	8	13LBx15	TL	19.0	391	792	1420	310
	10	13LBx15	TL	19.0	391	792	1680	410
	12	13LBx15	TL	19.0	391	792	1940	480
	16	13LBx15	TL	19.0	391	792	2460	620
33x15.50-16.5	12	12.00	TL	20.0	394	838	3100	415
	14	12.00	TL	20.0	394	838	3390	480
	18	12.00	TL	20.0	394	838	3970	620
15-22.5 (385/65-22.5)	12	11.75	TL	21.0	389	1095	4375	480
	16	11.75	TL	21.0	389	1095	6900	700
	18	11.75	TL	21.0	389	1095	7750	800
15-22.5HS (385/65-22.5HS)	16	11.75	TL	21.0	389	1095	4250 (65km/h)	260 (65km/h)
	18	11.75	TL	21.0	389	1095	5000 (65km/h)	310 (65km/h)
10-16.5	10	8.25	TL	19.0	264	773	2135	520
	12	8.25	TL	19.0	264	773	2375	620
12-16.5	10	9.75	TL	19.0	307	831	2540	450
	12	9.75	TL	19.0	307	831	2865	550
14-17.5	14	10.50	TL	20.0	349	921	3875	550
15-19.5	14	11.75	TL	20.0	389	1019	4565	480

HAL5 L-5

- Applications: skid steer equipment in scrap yards, recycling operations, mining, etc.
- Excellent cut, chip and tear resistance suitable for rough and hard concrete surface.
- The deep tread providing an extended tire life-cycle and excellent sidewall protection.



Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions		Load Capacity (kg)	Inflation Pressure (kPa)
					SW (mm)	OD (mm)	10km/h	10km/h
10-16.5	10	8.25	TL	35.0	264	773	2135	520
	12	8.25	TL	35.0	264	773	2375	620
12-16.5	12	9.75	TL	35.0	307	831	2865	550
	14	9.75	TL	35.0	307	831	3075	620

SKS4 L-4

- Applications: skid steer, backhoe loader, telehandler, aerial boom lift, scissor lift, compact tractor, front backhoe, 3-wheel forklift, rock service.
- The block pattern tire specially designed for construction applications.
- Ideal for paved surfaces and heavy-duty service.
- Excellent cut and chip resistance as well as top rim protection.



Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions		Load Capacity (kg)	Inflation Pressure (kPa)	Max Speed (km/h)
					SW (mm)	OD (mm)			
10-16.5	10	8.25	TL	27.0	264	773	2135	520	10
12-16.5	12	9.75	TL	33.0	307	831	2865	550	10
14-17.5	14	10.50	TL	37.0	349	921	3875	550	10
15-19.5	14	11.75	TL	37.0	389	1019	4565	480	10
12.5/80-18	12	W9	TL	30.0	308	985	2650	370	30
	14	W9	TL	30.0	308	985	2910	430	30
16.9/24	12	DW15	TL	24.0	430	1310	3200	250	40
	14	DW15	TL	24.0	430	1310	3530	300	40
16.9/28	12	DW15	TL	24.0	430	1310	3400	250	40
	14	DW15	TL	24.0	430	1310	3765	300	40
18.4/26	12	DW16	TL	27.0	467	1426	3500	250	40
	14	DW16	TL	27.0	467	1426	3875	290	40
19.5/24	12	DW16L	TL	27.0	490	1310	3450	230	40
	14	DW16L	TL	27.0	490	1310	3750	260	40
21L-24	14	DW18L	TL	27.0	540	1385	4125	250	40

HUL5 L-5

- Applications: skid steer, backhoe loader, telehandler, mining, rock service.
- The special tread compound leading to exceptional cut and chip resistance along with excellent wear resistance on all types of terrains.
- The extra deep tread with wider and sturdier blocks providing best traction, stability, and puncture resistance.



Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions		Load Capacity (kg)	Inflation Pressure (kPa)	Max Speed (km/h)
					SW (mm)	OD (mm)			
10-16.5	10	8.25	TL	27.0	264	773	2135	520	10
12-16.5	12	9.75	TL	33.0	307	831	2865	550	10
14-17.5	14	10.50	TL	37.0	349	921	3875	550	10
15-19.5	14	11.75	TL	37.0	389	1019	4565	480	10
19.5/24	14	16.00	TL	37.0	513	1333	5200	480	10
19.5/24	14	16.00	TL	37.0	513	1333	3447	235	40

SKSRIB

- Application: skid steer and other small industrial vehicles in sand operations.
- The sandy rib tire producing good resistance to abrasion and tear with maximum traction and high flotation.



Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions		Load Capacity (kg)	Inflation Pressure (kPa)
					SW (mm)	OD (mm)	10km/h	10km/h
10-16.5	10	8.25	TL	12.0	264	773	2135	520
	12	8.25	TL	12.0	264	773	2375	620
12-16.5	10	9.75	TL	13.5	307	831	2540	450
	12	9.75	TL	13.5	307	831	2865	550

SKSR4 R-4

- Applications: skid steer, compact loader, telehandler.
- Heavy-duty sidewall and large curb rib deliver more stability & traction, higher load capacity and greater puncture resistance on the most demanding conditions.
- Deep tread, buttressed lugs, full sidewall protection and an aggressive rim deflector to keep out debris.



Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions		Load Capacity (kg)	Inflation Pressure (kPa)
					SW (mm)	OD (mm)	40km/h	40km/h
18-22.5 (445/65-22.5)	16	14.00	TL	31.0	465	1190	4875	550
	18	14.00	TL	31.0	465	1190	5345	690
	20	14.00	TL	31.0	465	1190	6500	750



TRENK I-3

- Applications: trencher equipment, aerial work platform, portable forklift in lawn & garden.
- Best suited for applications on wet and dry surfaces.
- Large contact area to provide best traction and low pressure.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity (kg) 50km/h	Inflation Pressure (psi) 50km/h
26x12.00-12	10	10.50	TL	18.0	307 648	1630	450
31x15.50-15	8	13LBx15	TL	22.0	391 792	1250	310
(40050-15)	10	13LBx15	TL	22.0	391 792	1450	410
	12	13LBx15	TL	22.0	391 792	1650	510



IMPF3 F-3

- Applications: 2-wheel drive backhoe front, soil tillage operation, implement machinery, trailer.
- INDUSTRIAL RIB F3 is an agro-industrial rib-pattern tire designed for field and road transport.
- Provides excellent traction on hard soil, asphalt and concrete.
- Shock-fortified nylon-cord body resists impacts, cuts and punctures.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity (kg) 30km/h	Inflation Pressure (psi) 30km/h
11L-15	10	8LB	TL	13.5	230 810	1190	340
11L-16	10	8LB	TL	13.5	280 835	1240	340
14/575-16.1	10	11LB	TL	17.0	375 920	1450	280



SLR4A R-4

- Applications: backhoe front, telehandler, compact loader, compact dumper.
- EXTRA HEAVY CASING-Provides increased durability, larger cut and chip resistance, and extended service life.
- SPEPPED REINFORCED LUGS-Provides excellent stability, traction and self-cleaning.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity (kg) 30km/h	Inflation Pressure (psi) 30km/h
10.5/80-18	10	W9	TL	22.0	274 885	1935	370
	12	W9	TL	22.0	274 885	2160	430
12.5/80-18	12	W9	TL	27.0	308 965	2625	370
	14	W9	TL	27.0	308 965	2870	430



SLR4 R-4

- Applications: backhoe loader, telehandler, tractor.
- Particularly designed for digging and loading operations as well as municipality and maintenance applications.
- EXTRA HEAVY CASING-Provides increased durability, larger cut and chip resistant, and extended service life.
- SPEPPED REINFORCED LUGS-Provides excellent stability, traction and self-cleaning.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity (kg) 40km/h	Inflation Pressure (psi) 40km/h
14.9-24	12	W13	TL	26.0	378 1265	2900	290
16.9-24	12	W15L	TL	26.0	430 1335	3250	260
16.9-28	12	W14L	TL	26.0	430 1435	3450	260
16.9-30	12	DW15L	TL	27.0	440 1470	3650	255
18-24	12	W16L	TL	27.0	467 1374	3750	250
18-26	12	W16L	TL	27.0	467 1426	3875	250
18-28	12	W16L	TL	27.0	467 1477	4000	250
18-30	12	DW16L	TL	27.0	467 1510	4125	250
17.5L-24	12	W15L	TL	26.0	445 1245	3170	260
19.5L-24	12	W16L	TL	27.0	495 1314	3450	230
21L-24	12	DW18A	TL	27.0	553 1378	3875	220
21L-28	12	W18L	TL	27.0	550 1530	4000	210



DFMP L-3

- Applications: telehandler and backhoe loader.
- Increased tire life-environmentally friendly.
- Protective shoulder rib and low profile vertical sidewall reducing sidewall damage.
- Non-directional tread pattern reducing inventory carrying costs.
- New tread design reducing ground compaction and surface pressure on hard surfaces.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity (kg) 10km/h	Inflation Pressure (psi) 10km/h
370/75-28	14	11.00	TL	34.0	368 1278	5450	500
	16	11.00	TL	34.0	368 1278	5950	575
400/75-28	16	12.00	TL	34.0	399 1328	6500	525
	18	12.00	TL	34.0	399 1328	7000	600



TIMP R-1

- Applications: multipurpose truck (MPT), tractor, telehandler, backhoe loader, compact loader.
- Traction pattern, suitably designed for on and off-the road use, in all weather conditions particularly suitable for operations on muddy ground.
- Patterns design and strong carcass engineered to provide excellent traction to drive wheels, self-cleaning properties and extra cut-chip resistance.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity (kg) 30km/h	Inflation Pressure (psi) 30km/h
15.5/80-24	12	W13	TL	35.0	394 1240	2900	300
(40080-24)	14	W13	TL	35.0	394 1240	3150	350
	16	W13	TL	35.0	394 1240	3300	400



INTR1 R-1

- Applications: MPT, 2WD-tractor, telehandler, backhoe loader, compact loader.
- An agro-industrial tire suitable for field and road transport, municipality/maintenance operations as well as soil tillage applications depending on the tire size.
- Traction pattern, suitably designed for on and off-the road use, in all weather conditions.
- Patterns engineered to provide excellent traction to drive wheels and excellent self-cleaning properties.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity (kg) 30km/h	Inflation Pressure (psi) 30km/h
10.0/75-15.3	10	9.00	TL	28.0	264 760	1525	390
11.5/80-15	12	8.00	TL	28.0	290 865	2145	410
11.5/80-15.3	12	9.00	TL	28.0	290 865	2145	410
12.5/80-15.3	14	9.00	TL	28.0	307 925	2425	410



INTR4 R-4/I-3

- Applications: MPT, 2WD-tractor, telehandler, backhoe loader, compact loader.
- An agro-industrial tire suitable for field and road transport, municipality/maintenance operations as well as soil tillage applications depending on the tire size.
- Traction pattern, suitably designed for on and off-the road use, in all weather conditions.
- Patterns engineered to provide excellent traction to drive wheels and excellent self-cleaning properties.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity (kg) 40km/h	Inflation Pressure (psi) 40km/h
405/70-20	14	13.00	TL	30.0	410 1075	3750	350
(16/70-20)	16	13.00	TL	30.0	410 1075	3970	400
405/70-24	14	13.00	TL	30.0	410 1175	3950	350
(16/70-24)	16	13.00	TL	30.0	410 1175	4170	400
18-19.5	16	14.00	TL	24.0	460 1105	4700	600
(445/65D19.5)	18	14.00	TL	24.0	460 1105	5460	725



NMT IND-3

- All-terrain tire suitable for military vehicles, such as nuclear material transporter.
- Energy-saving rolling resistance, low temperature sensitivity, good stability, good traction, enhanced riding comfort.
- Cushioned compound and shock resistance.
- Reduced wear for longer life, improved mobility.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity (kg) 40km/h	Inflation Pressure (psi) 40km/h
355/65-15(350-15)	24	9.75x15	TL	23.0	372 861	6000	1000



DUMAX568 L-3

- Applications: loader, dozer used in construction stockpile & truck-loading.
- Radial design producing good ground grasping and traction in harsh condition, such as construction area, mine sites, quarry etc.
- Excellent traction and stability, delivering exceptional operator comfort.
- Excellent resistance to damage and longer life.

Size	SR	Load Index	RIM	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm)	Load Capacity (kg)	Inflation Pressure (kPa)
15.5R25	★	169A2	12.00/1.3	TL	24.0	395	1275	5800
	★★	176A2	12.00/1.3	TL	24.0	395	1275	7100
17.5R25	★	176A2	14.00/1.5	TL	26.0	420	1487	7100
	★★	182A2	14.00/1.5	TL	26.0	420	1487	8500
20.5R25	★	186A2	17.00/2.0	TL	28.5	512	1517	9500
	★★	192A2	17.00/2.0	TL	28.5	512	1517	11500
23.5R25	★	195A2	19.50/2.5	TL	32.0	590	1610	12150
	★★	201A2	19.50/2.5	TL	32.0	590	1610	14500
26.5R25	★	202A2	22.00/3.0	TL	35.0	673	1750	15000
	★★	209A2	22.00/3.0	TL	35.0	673	1750	18500

W-1 E-3/L-3



- Applications: loader, dozer, earthmover, grader, scraper operating under the relatively severe conditions.
- The tread compound providing cut-and-chip-resistant properties and suits best for loading and dozing operations.
- Aggressive, durable lug design, non-directional tread design and wide base construction, which can provide high flotation, excellent traction, improved stability and reduced ground pressure.
- The specially-formulated synthetic rubber compound can offer excellent cutting and heat resistance and help to prevent sidewall cracking.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm)	Load Capacity (kg)	Inflation Pressure (kPa)
1300-24	12	10.00	TT/TL	24.0	350	1350	5600*3000
1400-24	16	10.00	TT/TL	25.5	375	1370	7300*4000
	20	10.00	TT/TL	25.5	375	1370	8500*4625
	24	10.00	TT/TL	25.5	375	1370	9500*5150
	28	10.00	TT/TL	25.5	375	1370	10000*5600
1400-25	32	10.00	TT/TL	25.5	375	1370	10900*6150
	16	10.00/1.5	TT/TL	25.5	375	1370	7300*4000
	20	10.00/1.5	TT/TL	25.5	375	1370	8500*4625
	24	10.00/1.5	TT/TL	25.5	375	1370	9500*5150
	28	10.00/1.5	TT/TL	25.5	375	1370	10000*5600
	32	10.00/1.5	TT/TL	25.5	375	1370	10900*6150
1600-24	24	11.25/2.0	TT/TL	28.5	430	1495	10600*6000
	28	11.25/2.0	TT/TL	28.5	430	1495	11500*6700
	32	11.25/2.0	TT/TL	28.5	430	1495	12500*7300
1600-25	24	11.25/2.0	TT/TL	28.5	430	1495	10600*6000
	28	11.25/2.0	TT/TL	28.5	430	1495	11500*6700
	32	11.25/2.0	TT/TL	28.5	430	1495	12500*7300
1800-24	24	13.00/2.5	TT/TL	31.5	500	1615	12500*7300
	28	13.00/2.5	TT/TL	31.5	500	1615	13600*8000
	32	13.00/2.5	TT/TL	31.5	500	1615	15000*8750
	36	13.00/2.5	TT/TL	31.5	500	1615	16000*9250
	40	13.00/2.5	TT/TL	31.5	500	1615	17000*9700
1800-25	24	13.00/2.5	TT/TL	31.5	500	1615	12500*7300
	28	13.00/2.5	TT/TL	31.5	500	1615	13600*8000
	32	13.00/2.5	TT/TL	31.5	500	1615	15000*8750
	36	13.00/2.5	TT/TL	31.5	500	1615	16000*9250
	40	13.00/2.5	TT/TL	31.5	500	1615	17000*9700
17.5-25	16	14.00/1.5	TT/TL	25.5	445	1350	7300*4250
	20	14.00/1.5	TT/TL	25.5	445	1350	8250*5000
20.5-25	24	14.00/1.5	TT/TL	25.5	445	1350	9250*5600
	16	17.00/2.0	TT/TL	30.0	520	1490	8250*5450
	20	17.00/2.0	TT/TL	30.0	520	1490	9500*6000
	24	17.00/2.0	TT/TL	30.0	520	1490	10300*6700
23.5-25	16	19.50/2.5	TT/TL	31.5	595	1615	9500*6150
	20	19.50/2.5	TT/TL	31.5	595	1615	10900*7300
	24	19.50/2.5	TT/TL	31.5	595	1615	12500*8000
	28	19.50/2.5	TT/TL	31.5	595	1615	13600*8750
	32	19.50/2.5	TT/TL	31.5	595	1615	14000*9250
26.5-25	24	22.00/3.0	TT/TL	35.0	675	1750	15500*10000
	32	22.00/3.0	TT/TL	35.0	675	1750	17000*11200
29.5-25	28	25.00/3.5	TL	38.0	750	1875	17500*11500
	34	25.00/3.5	TL	38.0	750	1875	20000*12950
29.5-29	28	25.00/3.5	TL	38.0	750	1875	19000*12150
	34	25.00/3.5	TL	38.0	750	1875	21200*14000
1670-20	14	13.00	TT/TL	23.0	410	1075	5150*2900
1670-24	14	13.00	TT/TL	25.0	410	1175	5600*3350

W-2 E-3/L-3



- Applications: loader, dozer, earthmover, grader, scraper operating under the relatively severe conditions.
- BLOCK PATTERN TYRE SERIES suitable to be operated under many conditions.
- Aggressive, durable lug design, non-directional tread design and wide base construction, can provide high flotation, excellent traction, improved stability and reduced ground pressure.
- The specially-formulated synthetic rubber compound can offer excellent cutting and heat resistance and help to prevent sidewall cracking.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm)	Load Capacity (kg)	Inflation Pressure (kPa)
1600-24	24	11.25/2.0	TT/TL	28.5	430	1495	10600*6000
	28	11.25/2.0	TT/TL	28.5	430	1495	11500*6700
	32	11.25/2.0	TT/TL	28.5	430	1495	12500*7300
1600-25	24	11.25/2.0	TT/TL	28.5	430	1495	10600*6000
	28	11.25/2.0	TT/TL	28.5	430	1495	11500*6700
	32	11.25/2.0	TT/TL	28.5	430	1495	12500*7300
1800-24	24	13.00/2.5	TT/TL	31.5	500	1615	12500*7300
	28	13.00/2.5	TT/TL	31.5	500	1615	13600*8000
	32	13.00/2.5	TT/TL	31.5	500	1615	15000*8750
	36	13.00/2.5	TT/TL	31.5	500	1615	16000*9250
	40	13.00/2.5	TT/TL	31.5	500	1615	17000*9700
1800-25	24	13.00/2.5	TT/TL	31.5	500	1615	12500*7300
	28	13.00/2.5	TT/TL	31.5	500	1615	13600*8000
	32	13.00/2.5	TT/TL	31.5	500	1615	15000*8750
	36	13.00/2.5	TT/TL	31.5	500	1615	16000*9250
	40	13.00/2.5	TT/TL	31.5	500	1615	17000*9700
15.5-25	12	12.00/1.3	TT/TL	24.0	395	1275	5600*3750
	16	12.00/1.3	TT/TL	24.0	395	1275	6500*3750
17.5-25	16	14.00/1.5	TT/TL	24.0	445	1350	7300*4250
	20	14.00/1.5	TT/TL	24.0	445	1350	8250*5000
	24	14.00/1.5	TT/TL	24.0	445	1350	9250*5600
20.5-25	16	17.00/2.0	TT/TL	29.0	520	1490	8250*5450
	20	17.00/2.0	TT/TL	29.0	520	1490	9500*6000
	24	17.00/2.0	TT/TL	29.0	520	1490	10300*6700
23.5-25	16	19.50/2.5	TT/TL	30.0	595	1615	9500*6150
	20	19.50/2.5	TT/TL	30.0	595	1615	10900*7300
	24	19.50/2.5	TT/TL	30.0	595	1615	12500*8000
	28	19.50/2.5	TT/TL	30.0	595	1615	13600*8750
26.5-25	24	22.00/3.0	TT/TL	32.0	675	1750	14000*9250
	32	22.00/3.0	TT/TL	32.0	675	1750	15500*10000
	36	22.00/3.0	TT/TL	32.0	675	1750	17000*11200
29.5-25	28	25.00/3.5	TL	32.0	750	1875	17500*11500
	34	25.00/3.5	TL	32.0	750	1875	20000*12950
29.5-29	28	25.00/3.5	TL	36.0	750	1875	19000*12150
	34	25.00/3.5	TL	36.0	750	1875	21200*14000

W-3A E-2



- Applications: excavators in road construction works, soft and muddy ground.
- Wide tread pattern providing good floating and excellent driving properties.
- The strong casing providing extraordinary resistance to impacts and shocks even in heavy-duty operations.
- Special tread compound producing particular resistance to cuts and snags, extremely strong traction, good self-cleaning.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm)	Load Capacity (kg)	Inflation Pressure (kPa)
900-20	14	7.00	TT	22.0	262	1024	4385*2770
	16	7.00	TT	22.0	262	1024	4745*3000
	18	7.00	TT	22.0	262	1024	5105*3230
1000-20	16	7.50	TT	23.0	280	1060	4945*3230
	18	7.50	TT	23.0	280	1060	5195*3365
	20	7.50	TT	23.0	280	1060	5445*3505
1100-20	16	8.00	TT	29.5	296	1100	5405*3555
	18	8.00	TT	29.5	296	1100	5805*3850
	20	8.00	TT	29.5	296	1100	6205*4150

W-3B E-3

- Applications: heavy duty excavator and forklift in road construction works, soft and muddy ground, crane on road and port.
- Wide tread pattern providing good floating and excellent driving properties, speeding up to 70km/h.
- The strong casing providing extraordinary resistance to impacts and shocks even in heavy-duty operations.
- Special tread compound producing particular resistance to cuts and snags, extremely strong traction, good self-cleaning.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity _{kg} ^{10km/h}	Inflation Pressure _{kg/cm²} ^{10km/h}
9.00-20	16	7.00	TT	25.0	259 1038	3000	790
	18	7.00	TT	25.0	259 1038	3230	870
10.00-20	18	7.50	TT	30.0	278 1073	3365	820
	20	7.50	TT	30.0	278 1073	3505	860
11.00-20	18	8.00	TT	29.5	296 1100	3850	820
	20	8.00	TT	29.5	296 1100	4150	870

W-3C E-3

- Applications: heavy duty excavator and forklift in road construction works, soft and muddy ground, and highway crane on road and port.
- Wide tread pattern providing good floating and excellent driving properties, speeding up to 70km/h.
- The strong casing providing extraordinary resistance to impacts and shocks even in heavy-duty operations.
- Special tread compound producing particular resistance to cuts and snags, extremely strong traction, good self-cleaning.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity _{kg} ^{70km/h}	Inflation Pressure _{kg/cm²} ^{70km/h}
12.00-24	20	8.50	TT	22.0	316 1130	3750	550
	24	8.50	TT	22.0	316 1130	4350	600

W-3D G-2

- Applications: scraper and motor grader in city and country maintenance work, construction and mine applications.
- Pattern design producing excellent traction and self-cleaning features.
- A special compound enabling an extended tire life-cycle and heavy-duty service.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity _{kg} ^{10km/h/40km/h}	Inflation Pressure _{kg/cm²} ^{10km/h/40km/h}
13.00-24	12	8.00	TT/TL	25.0	335 1275	5600*2725	450*300
	16	8.00	TT/TL	25.0	335 1275	6500*3275	600*425
14.00-24	12	8.00	TT/TL	25.0	360 1345	6300*3075	425*275
	16	8.00	TT/TL	25.0	360 1345	7300*3650	550*375
16.00-24	16	10.00VA	TT/TL	28.5	425 1460	8250*4500	425*325

W-3DN G-2

- Applications: scraper and motor grader in city and country maintenance work, construction and mine applications.
- The stronger, larger and more durable casing designed to extend life service and maximize equipment capacities, than W-3D.
- Pattern design producing excellent traction and self-cleaning features.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity _{kg} ^{10km/h/40km/h}	Inflation Pressure _{kg/cm²} ^{10km/h/40km/h}
13.00-24	12	8.00	TT/TL	28.0	366 1298	5600*2725	450*300
	16	8.00	TT/TL	28.0	366 1298	6500*3275	600*425
14.00-24	12	8.00	TT/TL	28.0	398 1370	6300*3075	425*275
	16	8.00	TT/TL	28.0	398 1370	7300*3650	550*375

W-3E G-2

- Applications: scraper and motor grader in city and country maintenance work, construction and mine applications.
- Precision-angled bars maximizing traction in soft soil and providing long wear.
- Open shoulder grooves providing self-cleaning, excellent traction and less slipping.
- Tough and durable casing producing the most widely retreaded tire in the industry.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity _{kg} ^{40km/h}	Inflation Pressure _{kg/cm²} ^{40km/h}
15.5-25	12	12.00/1.3	TT/TL	23.5	395 1275	2650	225
	16	12.00/1.3	TT/TL	23.5	395 1275	3200	325
17.5-25	12	14.00/1.5	TT/TL	23.0	445 1350	2900	200
	16	14.00/1.5	TT/TL	23.0	445 1350	3350	275
	20	14.00/1.5	TT/TL	23.0	445 1350	3650	325
20.5-25	12	17.00/2.0	TT/TL	26.5	520 1490	3550	175
	16	17.00/2.0	TT/TL	26.5	520 1490	4000	225
	20	17.00/2.0	TT/TL	26.5	520 1490	4500	275
23.5-25	12	19.00/2.5	TT/TL	30.5	595 1615	4000	150
	16	19.00/2.5	TT/TL	30.5	595 1615	4750	200
	20	19.00/2.5	TT/TL	30.5	595 1615	5450	250

W-3EN G-2

- Applications: scraper and motor grader in city and country maintenance work, construction and mine applications.
- The strong, larger and durable casing designed to extend life service and maximize equipment capacities.
- Pattern design producing excellent traction and self-cleaning features.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity _{kg} ^{40km/h}	Inflation Pressure _{kg/cm²} ^{40km/h}
17.5-25	12	14.00/1.5	TT/TL	26.0	464 1366	2900	200
	16	14.00/1.5	TT/TL	26.0	464 1366	3350	275
	20	14.00/1.5	TT/TL	26.0	464 1366	3650	325

W-4 E-4/IND-4

- Applications: Port Equipment, including Empty Container Handler, Reach Stacker, Straddle & Shuttle Carrier, Rubber.
- Tyre Gantry (RTG), Automated Guide Vehicles (AGV), Harbour Mobile Crane (HMC).
- Special compound and design suitable for handling equipment operating in airport, yard, port and so on.
- Deep tread pattern and wide riding area providing good cutting and wear resistances, improving ride properties on gravel road.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity _{kg} ^{10km/h/30km/h}	Inflation Pressure _{kg/cm²} ^{10km/h/30km/h}
12.00-24	16	8.50	TT/TL	35.0	335 1272	6250*3250	675*450
	20	8.50	TT/TL	35.0	335 1272	6900*3650	825*550
	24	8.50	TT/TL	35.0	335 1272	7600*4000	975*650
	28	8.50	TT/TL	35.0	335 1272	8250*4300	1075*750
14.00-24	20	10.00W	TT/TL	44.5	404 1412	8500*4625	700*475
	24	10.00W	TT/TL	44.5	404 1412	9500*5150	850*575
	28	10.00W	TT/TL	44.5	404 1412	10000*5600	925*650
	32	10.00W	TT/TL	44.5	404 1412	10400*5950	1000*725
14.00-25	20	10.00	TT/TL	44.5	406 1412	8500*4625	700*475
	24	10.00	TT/TL	44.5	406 1412	9500*5150	850*575
	28	10.00	TT/TL	44.5	406 1412	10000*5600	925*650
	32	10.00	TT/TL	44.5	406 1412	10900*6150	1050*750
16.00-25	28	11.25/2.0	TT/TL	50.0	430 1495	11500*6700	750*575
	32	11.25/2.0	TT/TL	50.0	430 1495	12500*7300	875*650
	36	11.25/2.0	TT/TL	50.0	430 1495	13600*7750	975*725
	40	11.25/2.0	TT/TL	50.0	430 1495	14500*8150	1075*750
18.00-25	28	13.00/2.5	TL	54.0	500 1615	13600*8000	650*500
	32	13.00/2.5	TL	54.0	500 1615	15000*8750	750*575
	36	13.00/2.5	TL	54.0	500 1615	16000*9250	850*625
	40	13.00/2.5	TL	54.0	500 1615	17000*9750	950*700
	48	13.00/2.5	TL	54.0	500 1615	19000*10250	1100*900
21.00-25	28	15.00	TL	57.0	570 1800	16500*9500	575*425
	32	15.00	TL	57.0	570 1800	17500*10300	650*500
	36	15.00	TL	57.0	570 1800	19500*10900	750*550
	40	15.00	TL	57.0	570 1800	20600*11800	825*625
24.00-29	30	17.00	TL	54.0	655 1975	21800*12500	525*400
	36	17.00	TL	54.0	655 1975	24600*14000	625*475
	42	17.00	TL	54.0	655 1975	27400*15900	725*550
	48	17.00	TL	54.0	655 1975	30200*18400	825*625
18.00-33	32	13.00/2.5	TL	53.5	500 1820	17500*10000	750*575
	36	13.00/2.5	TL	53.5	500 1820	18500*10600	825*625
	42	13.00/2.5	TL	53.5	500 1820	20000*11500	975*725
	44	13.00/2.5	TL	53.5	500 1820	21000*12100	1050*775

W-4A E-4



- Applications: heavy dump truck & scraper operation on relatively tough road surface in areas like mining areas, tunnel, quarry, construction site, etc.
- Deep tread pattern and wide riding area providing good cutting and wear resistances, improving ride properties on gravel road.
- Special compound and design extending the tire service life.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity (kg) 10km/h*50km/h	Inflation Pressure (kPa) 10km/h*50km/h
18.00-33	32	13.00/2.5	TL	53.5	500 1820	17500*10000	750*575
	36	13.00/2.5	TL	53.5	500 1820	18500*10600	825*625
	42	13.00/2.5	TL	53.5	500 1820	20000*11500	975*725
16.00-25	28	11.25/2.0	TL	50.0	430 1495	11500*6700	750*575
	32	11.25/2.0	TL	50.0	430 1495	12500*7300	875*650
	36	11.25/2.0	TL	50.0	430 1495	13600*7750	975*725
	40	11.25/2.0	TL	50.0	430 1495	14500*8150	1075*775
18.00-25	28	13.00/2.5	TL	54.0	500 1615	13600*8000	650*500
	32	13.00/2.5	TL	54.0	500 1615	15000*8750	750*575
	36	13.00/2.5	TL	54.0	500 1615	16000*9250	850*625
	40	13.00/2.5	TL	54.0	500 1615	17000*9750	950*700
	48	13.00/2.5	TL	54.0	500 1615	19000*10250	1100*900
21.00-25	28	15.00	TL	57.0	570 1800	16500*9500	575*425
	32	15.00	TL	57.0	570 1800	17500*10300	650*500
	36	15.00	TL	57.0	570 1800	19500*10900	750*550
	40	15.00	TL	57.0	570 1800	20600*11800	805*625
21.00-33	42	15.00	TL	54.0	570 1955	22400*12400	775*625
	54	15.00	TL	54.0	570 1955	32500*14200	875*725
21.00-35	36	15.00/3.0	TL	54.0	570 2005	23000*12850	750*550
	40	15.00/3.0	TL	54.0	570 2005	24300*14000	825*625
	44	15.00/3.0	TL	54.0	570 2005	25000*14500	900*675
24.00-35	42	15.00/3.0	TL	57.0	653 2130	29000*16500	750*550
	48	15.00/3.0	TL	57.0	653 2130	31500*18500	850*650

W-4B E-4



- Applications: underground mining and port equipment, including Straddle & Shuttle Carrier, RTG Reach Stacker, Empty Container Handler, AGV, HMC, LHD.
- Deep tread, the extra thick sidewall and the tough casing providing exceptional durability minimizing the risk of punctures and accidental damages.
- Excellent cut and chip resistance, which is particularly suitable for rough and hard surfaces.
- Specially designed rim guard ensuring protection against flats and wheel damage in the rim flange area.
- Deeper tread making the longer service life than W-4.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity (kg) 10km/h*50km/h	Inflation Pressure (kPa) 10km/h*50km/h
12.00-24	16	8.50	TT/TL	35.0	335 1272	6250*3250	575*450
	20	8.50	TT/TL	35.0	335 1272	6900*3650	625*550
	24	8.50	TT/TL	35.0	335 1272	7600*4000	975*650
	28	8.50	TT/TL	35.0	335 1272	8250*4300	1075*750
14.00-24	20	10.00W	TT/TL	44.5	404 1412	8500*4625	700*475
	24	10.00W	TT/TL	44.5	404 1412	9500*5150	850*575
	28	10.00W	TT/TL	44.5	404 1412	10000*5500	925*650
	32	10.00W	TT/TL	44.5	404 1412	10400*5950	1000*725
18.00-25	28	13.00/2.5	TL	75.0	500 1615	13600*8000	650*500
	32	13.00/2.5	TL	75.0	500 1615	15000*8750	750*575
	36	13.00/2.5	TL	75.0	500 1615	16000*9250	850*625
	40	13.00/2.5	TL	75.0	500 1615	17000*9750	950*700
	48	13.00/2.5	TL	75.0	500 1615	19000*10250	1100*900

W-5 E-3



- Applications: heavy-duty scraper and loader operating on mining areas, tunnel, quarry, construction site, etc.
- Center riding rib providing a smooth ride and improving lateral stability.
- Deep, non-directional, rock service tread designed for the challenges of large equipment demands, such as long-time service, self-cleaning, cut resistance, etc.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity (kg) 10km/h*50km/h	Inflation Pressure (kPa) 10km/h*50km/h
33.25-29	26	27.00/3.5	TL	38.0	845 2090	20600*13600	350*275
	32	27.00/3.5	TL	38.0	845 2090	23600*15000	450*325
33.25-35	42	27.00/3.5	TL	43.0	845 2240	25750*16000	450*325
	38	27.00/3.5	TL	43.0	845 2240	28000*17000	550*400
	44	27.00/3.5	TL	43.0	845 2240	32300*18600	625*475
33.5-33	32	28.00/4.0	TL	43.0	850 2240	25750*16500	425*325
	38	28.00/4.0	TL	43.0	850 2240	29000*18500	525*400
	44	28.00/4.0	TL	43.0	850 2240	32300*19800	625*475
37.25-35	36	31.00/4.0	TL	43.0	945 2390	30750*19500	450*325
	42	31.00/4.0	TL	43.0	945 2390	33500*21800	525*400
37.5-33	36	32.00/4.5	TL	43.0	950 2390	31500*20000	450*325
	42	32.00/4.5	TL	43.0	950 2390	34500*22400	525*400

W-5A L-4



- Applications: giant loader in the ore and coal mine sites.
- Extra deep tread producing excellent rock type damage resistance and long tread life.
- Open non-directional tread pattern providing all round traction with excellent self-cleaning.
- Cut Resistant Breaker (CRB) construction providing increased strength and durability without sacrificing heat resistance.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity (kg) 2.5km/h*5km/h	Inflation Pressure (kPa) 2.5km/h*5km/h
5080-57	68	36.00/6.0	TL	97.0	1260 3540	102800*90000	650*650
5280-57	72	36.00/6.0	TL	97.0	1320 3550	116300*102000	650*650
5580-57	72	44.00/6.0	TL	100.0	1400 3560	120000*100000	650*650
55580-57	76	44.00/6.0	TL	100.0	1400 3720	137800*117800	750*750
53585-57	76	44.00/6.0	TL	100.0	1350 3920	129200*115600	750*750
5655-57	62	52.00/6.0	TL	100.0	1650 3730	121300*105000	600*600
4565-45	58	36.00/4.5	TL	116.0	1015 2350	50000 (10km/h)	675 (10km/h)

W-5B L-4



- Applications: giant loader in the ore and coal mine sites.
- Extra deep tread producing excellent rock type damage resistance and long tread life.
- Open non-directional tread pattern providing all round traction with excellent self-cleaning.
- Cut Resistant Breaker (CRB) construction providing increased strength and durability without sacrificing heat resistance.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity (kg) 2.5km/h*5km/h	Inflation Pressure (kPa) 2.5km/h*5km/h
5885-57	84	47.00/6.0	TL	100.0	1450 3928	142800*125000	790*790
7070-57	84	60.00/6.0	TL	100.0	1750 3928	199500*173000	800*800

W-5C L-4



- Applications: loader and dozer in quarry and harsh pavement.
- Non-directional pattern design for heavy duty rock service.
- Ideal tire for severe operations requiring reinforced cut resistance, sidewall protection and exceptional traction, excellent tread cleaning design.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity (kg) 10km/h	Inflation Pressure (kPa) 10km/h
17.5-25	16	14.00/1.5	TL	46.0	445 1400	7300	475
	20	14.00/1.5	TL	46.0	445 1400	8250	575
	24	14.00/1.5	TL	46.0	445 1400	9250	700



W-6 L-5

- Applications: loader & earthmover used in the harsh conditions, such as construction and mining areas.
- Extra deep tread and strong casing design providing excellent rock type damage resistance and long tread life in heavy duty.
- Open non-directional tread pattern producing all round traction with excellent self-cleaning.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity _{kg} 10km/h	Inflation Pressure _{PSI} 10km/h
17.5-25	20	14.00/1.5	TL	62.0	445 1350	8250	575
20.5-25	24	14.00/1.5	TL	62.0	445 1350	9250	700
23.5-25	20	17.00/2.0	TL	69.0	520 1490	9500	450
24	24	17.00/2.0	TL	69.0	520 1490	10300	525
26.5-25	20	19.50/2.5	TL	76.0	595 1615	10900	375
28	24	19.50/2.5	TL	76.0	595 1615	12500	475
28	28	19.50/2.5	TL	76.0	595 1615	13600	550
29.5-25	24	22.00/3.0	TL	87.0	675 1750	14000	400
28	28	22.00/3.0	TL	87.0	675 1750	15500	475
32	32	22.00/3.0	TL	87.0	675 1750	17000	550
29.5-25	28	25.00/3.5	TL	92.0	750 1875	17500	425
34	34	25.00/3.5	TL	92.0	750 1875	20000	525
29.5-29	28	25.00/3.5	TL	92.0	750 1975	19000	425
34	34	25.00/3.5	TL	92.0	750 1975	21200	525
35/65-33	30	28.00/3.5	TL	97.0	890 2030	21200	425
36	36	28.00/3.5	TL	97.0	890 2030	23600	525
40	40	28.00/3.5	TL	97.0	890 2030	26500	625
48	48	28.00/3.5	TL	97.0	890 2030	29000	725
45/65-39	36	32.00/4.0	TL	116.0	1140 2410	34500	400
46	46	32.00/4.0	TL	116.0	1140 2410	41250	525
58	58	32.00/4.0	TL	116.0	1140 2410	47500	675
45/65-45	38	36.00/4.5	TL	116.0	1015 2350	38750	425
46	46	36.00/4.5	TL	116.0	1015 2350	43750	525
58	58	36.00/4.5	TL	116.0	1015 2350	50000	675



W-6A L-5

- Applications: giant loader in the ore and coal mine sites.
- Extra deep tread producing excellent rock type damage resistance and long tread life.
- Open non-directional tread pattern providing all round traction with excellent self-cleaning.
- Cut Resistant Breaker (CRB) construction providing increased strength and durability without sacrificing heat resistance.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity _{kg} 10km/h	Inflation Pressure _{PSI} 10km/h
50/65-61	62	40.00/4.5	TL	127	1270 2995	63000	650
67/560-61	84	46.00/5.5	TL	137	1690 3520	107300	690



W-6B L-4

- Applications: loader & earthmover used in the harsh conditions, such as construction and mining areas.
- Extra deep tread and strong casing design providing excellent rock type damage resistance and long tread life in heavy duty.
- Open non-directional tread pattern producing all round traction with excellent self-cleaning.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity _{kg} 10km/h	Inflation Pressure _{PSI} 10km/h
23.5-25	20	19.50/2.5	TL	54.0	595 1615	10900	375
24	24	19.50/2.5	TL	54.0	595 1615	12500	475
28	28	19.50/2.5	TL	54.0	595 1615	13600	550
26.5-25	24	22.00/3.0	TL	54.0	675 1750	14000	400
28	28	22.00/3.0	TL	54.0	675 1750	15500	475
32	32	22.00/3.0	TL	54.0	675 1750	17000	550



W-7 L-5S

- Applications: underground load-haul-dump (LHD), shuttle car in rocky harsh conditions of pit lane, tunnel, underground mines.
- Extra deep tread depth offering long tread life in extreme conditions.
- Smooth or slick tread design providing the maximum rock type damage resistance.
- Features Aralon Cut Resistant Breaker (CRB) construction, which provides increased strength and durability without sacrificing heat resistance.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity _{kg} 10km/h	Inflation Pressure _{PSI} 10km/h
10.00-20	14	8.00	TT/TL	30.5	279 1069	4250	650
16	16	8.00	TT/TL	30.5	279 1069	4600	750
12.00-20	16	8.50	TT/TL	56.0	315 1145	5450	700
20	20	8.50	TT/TL	56.0	315 1145	6350	875
24	24	8.50	TT/TL	56.0	315 1145	7500	975
12.00-24	20	8.50V	TT/TL	56.0	315 1245	6900	825
24	24	8.50V	TT/TL	56.0	315 1245	7500	975
14.00-24	20	10.00W	TT/TL	63.5	375 1370	8500	700
24	24	10.00W	TT/TL	63.5	375 1370	9600	850
28	28	10.00W	TT/TL	63.5	375 1370	10000	925
32	32	10.00W	TT/TL	63.5	375 1370	10900	1050
36	36	10.00W	TT/TL	63.5	375 1370	11400	1100
16.00-25	28	11.25/2.0	TL	71.0	430 1395	11500	750
32	32	11.25/2.0	TL	71.0	430 1395	12500	875
36	36	11.25/2.0	TL	71.0	430 1395	13600	975
40	40	11.25/2.0	TL	71.0	430 1395	14500	1075
18.00-25	32	13.00/2.5	TL	78.5	523 1666	15000	750
36	36	13.00/2.5	TL	78.5	523 1666	16000	850
40	40	13.00/2.5	TL	78.5	523 1666	17000	950
50	50	13.00/2.5	TL	78.5	523 1666	19500	1200
17.5-25	20	14.00/1.5	TL	62.0	445 1350	8250	800
24	24	14.00/1.5	TL	62.0	445 1350	9950	850
20.5-25	20	17.00/2.0	TL	69.0	520 1490	9500	450
24	24	17.00/2.0	TL	69.0	520 1490	10300	525
23.5-25	20	19.50/2.5	TL	76.0	595 1615	10900	375
24	24	19.50/2.5	TL	76.0	595 1615	12500	475
28	28	19.50/2.5	TL	76.0	595 1615	13600	550
26.5-25	36	22.00/3.0	TL	87.5	695 1750	18500	625
40	40	22.00/3.0	TL	87.5	695 1750	19800	750
50	50	22.00/3.0	TL	87.5	695 1750	23500	900
29.5-25	36	25.00/3.5	TL	95.0	750 1875	21200	550
40	40	25.00/3.5	TL	95.0	750 1875	22500	625
50	50	25.00/3.5	TL	95.0	750 1875	26700	775
29.5-29	36	25.00/3.5	TL	95.0	750 1975	22000	550
40	40	25.00/3.5	TL	95.0	750 1975	23600	625
50	50	25.00/3.5	TL	95.0	750 1975	26800	775
35/65-33	42	28.00/3.5	TL	97.0	890 2030	26500	625
48	48	28.00/3.5	TL	97.0	890 2030	29000	725
45/65-45	58	36.00/4.5	TL	116.0	1015 2350	50000	675



W-7A C-1

- Applications: compactor and roller tractor.
- Higher stability, wider contact area, and smooth profile for efficient compaction.
- Special compound providing high heat resistance and longer tire life.
- Low rolling resistance for economy performance.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity _{kg} 10km/h	Inflation Pressure _{PSI} 10km/h
7.50-15	14	6.00	TT	15.0	215 780	2850	825
9.00-20	16	7.00	TT	15.0	259 1018	4750	725
10.00-20	16	7.50	TT	16.0	278 1055	5300	800
11.00-20	18	8.00	TT	16.0	293 1085	6000	825
12.00-20	20	8.50	TT	18.0	315 1125	6750	900

W-8 E-7/C-1



- Variable compounds for different pattern and different applications.
- E-7 used in the sandy and desert areas, C-1 for compactor in road construction.
- E-7 special compound producing good resistance to the high temperature.
- Flat and wide foot print suitable for flotation applications on soft soil, orchards, etc.
- Tread specially designed to give minimum ground disturbance.
- Increased tread depth and strong carcass ensuring long life.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions SW (mm) OD (mm)	Load Capacity (kg) 10km/h/30km/h	Inflation Pressure (kPa) 10km/h/30km/h
1600-20	16	10.00W	TT/TL	15.0	420 1370	5650*3150	240*170
231-26	12	DW20	TT/TL	28.0	587 1580	5150*3650	240*170
	14	DW20	TT/TL	28.0	587 1580	5710*4050	275*200
	16	DW20	TT/TL	28.0	587 1580	6060*4330	350*230
2421	16	18.00/1.5	TT/TL	13.0	610 1370	5600*3875	240*170
2400-20.5	16	18.00/0.5	TT/TL	13.0	610 1370	5600*3875	240*170

W-9



- Applications: forklift vehicles operating in port, airport, factory and warehouse sites, etc.
- Special compound producing good cutting, wear resistances, long lift service.
- Wide and thick tread design providing good ground contact, traction and self-cleaning.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions SW (mm) OD (mm)	Load Capacity (kg) Drive/Steer 25km/h	Inflation Pressure (kPa) Drive/Steer 25km/h
8.25-15	12	6.50	TT	20.0	235 840	3490*2945	720
	14	6.50	TT	20.0	235 840	3775*3185	830
	16	6.50	TT	20.0	235 840	4050*3550	925
560x165-11	12	4.5x11	TT	16.0	165 560	1675*1000	970
680x180-15	12	5.0x15	TT	16.0	180 680	2005*1350	860

W-9A



- Applications: forklift vehicles operating in port, airport, factory and warehouse sites, etc.
- Special compound producing good cutting, wear resistances, long lift service.
- Wide and thick tread design providing good ground contact, traction and self-cleaning.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions SW (mm) OD (mm)	Load Capacity (kg) Drive/Steer 25km/h	Inflation Pressure (kPa) Drive/Steer 25km/h
7.00-9	10	5.00S	TT	11.0	190 590	1995*1685	860
8.25-12	12	7.00	TT	15.0	235 765	3060*2585	720

W-9B



- Applications: forklift vehicles operating in port, airport, factory and warehouse sites, etc.
- Special compound producing good cutting, wear resistances, long lift service.
- Wide and thick tread design providing good ground contact, traction and self-cleaning.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions SW (mm) OD (mm)	Load Capacity (kg) Drive/Steer 25km/h	Inflation Pressure (kPa) Drive/Steer 25km/h
5.00-8	8	3.50D	TT	10.0	137 470	1000*845	790
	10	3.50D	TT	10.0	137 470	1150*970	1000
18x7.8 (180/70-8)	14	4.33R	TT	10.0	173 465	1505*1270	970
	16	4.33R	TT	10.0	173 465	1695*1450	1000
6.00-9	10	4.00E	TT	10.0	160 540	1505*1270	860
6.50-10	10	5.00F	TT	11.0	175 590	1655*1400	790
7.00-12	12	5.00S	TT	14.0	190 675	2375*2005	860
7.00-15	12	5.50F	TT	15.0	200 750	2870*2420	860
7.50-15	12	6.00	TT	16.0	215 780	3075*2680	790
7.50-16	12	6.00G	TT	18.0	215 805	3195*2700	790
	14	6.00G	TT	18.0	215 805	3535*2995	925
	16	6.00G	TT	18.0	215 805	3875*3280	1000
8.15-15 (28x15)	12	7.00	TT	17.0	215 704	2790*2355	830
	14	7.00	TT	17.0	215 704	3050*2575	970
9.00-20	18	7.00	TT	22.0	259 1018	4685*2970	860
10.00-20 (290/95-20)	18	7.50	TT	23.0	280 1055	5195*3365	860
	20	7.50	TT	23.0	280 1055	6275*4815	930
	24	7.50	TT	23.0	280 1055	7385*5670	1025
12.00-20 (330/95-20)	20	8.50	TT	24.0	315 1125	6835*4200	860
	24	8.50	TT	24.0	315 1125	7650*4780	930
	28	8.50	TT	24.0	315 1125	8510*5460	1025
250-15 (250/70-15)	16	7.50	TT	20.0	250 735	4355*3350	825
	18	7.50	TT	20.0	250 735	4745*3650	960
	20	7.50	TT	20.0	250 735	5135*3950	1075
300-15 (315/70-15)	18	8.00	TT	22.0	300 840	5850*4500	850
	20	8.00	TT	22.0	300 840	6500*5000	900

W-10 LS-1/HF-2



- Applications: agricultural and forestry tractor, harvester, petroleum exploration vehicle (vibrator machine) and fuel truck
- Belted Steel construction for the forestry application to produce the puncture proof
- Deeper-tread flotation tires for maximum traction in the toughest conditions
- Special wide-arc design protecting sidewall from cuts and snags
- 23-degree angle bar for good contact and excellent traction

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions SW (mm) OD (mm)	Load Capacity (kg) 40km/h	Inflation Pressure (kPa) 40km/h
54x37.00-25	12	32.00	TL	37.0	935 1430	5890	240
	20	32.00	TL	37.0	935 1430	7660	380
66x43.00-25	16	36.00	TL	37.0	1050 1700	6100	290
	20	36.00	TL	37.0	1050 1700	6900	310

W-10A HF-1



- Applications: monster performance car.
- Low ply rating and low tread depth design lightening tires.
- Super wide tread design and special construction improving the tire stability and casing strength.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions SW (mm) OD (mm)	Load Capacity (kg) 50km/h	Inflation Pressure (kPa) 50km/h
66x43.00-25	10	36.00	TL	13.0	1050 1650	4500	170
	12	36.00	TL	13.0	1050 1650	5000	210

W-10B E-7/HF-1



- Applications: petroleum exploration vehicle (vibrator machine) and fuel truck.
- Low-sectional tire with super base providing:
 1. high traction performance on soft road surface.
 2. extreme stability.
 3. low tire press on ground lightly without sinking.
 4. promotion of the efficiency of off-the-road vehicles.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity (kg) 10km/h/50km/h	Inflation Pressure (kPa) 40km/h
66x44.00-25	16	36.00	TL	12.0	1075 1720	6150	280
	20	36.00	TL	12.0	1075 1720	7000	340

W-11 E-7



- Applications: off-road vehicles on sandy and desert areas, as well as paver and compactor machines.
- Special compound producing the resistance to extreme high temperature.
- Wide tread, round shoulder and streamlined pattern design providing stable ride, good floating force, excellent steering ability and uniform tread wear.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity (kg) 10km/h/50km/h	Inflation Pressure (kPa) 10km/h/50km/h
8.25-16	8	6.00	TT/TL	11.0	240 850	1500*980	250
9.00-16	8	6.50H	TT/TL	11.0	245 890	1700*975	245
21.00-25	16	15.00/3.0	TL	16.0	570 1685	10000*5800	245
	32	15.00/3.0	TL	16.0	570 1685	15450*9150	450

W-12 E-7



- Applications: off-road vehicles on sandy and desert areas, as well as paver and compactor machines.
- Special compound producing the resistance to extreme high temperature.
- Wide tread, round shoulder and streamlined pattern design providing stable ride, good floating force, excellent steering ability and uniform tread wear.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity (kg) 10km/h/50km/h	Inflation Pressure (kPa) 10km/h/50km/h
16.00-16	6	6.50H	TT/TL	8.0	355 1080	4000*2360	245
14.00-20	18	7.50V	TT/TL	9.0	375 1220	4125*2360	245
16.00-20	16	10.00W	TT/TL	15.0	419 1323	5450*3150	245
24.00-25	16	18.00/0.5	TT/TL	16.0	610 1370	5600*3875	240
24-21	16	18.00/1.5	TT/TL	16.0	610 1370	5600*3875	240
18.00-25	16	10.00/1.5	TL	14.0	470 1557	7750*4375	245
29.5-25	28	25.00/3.5	TL	21.0	750 1830	12535*10000	240
36.00-61	42	26.00/5.0	TL	26.0	990 3075	48000*26500	240
	50	26.00/5.0	TL	26.0	990 3075	55000*29870	290
	58	26.00/5.0	TL	26.0	990 3075	61000*33250	350

W-12A E-7



- Applications: off-road vehicles operating on sandy and desert areas.
- Special compound producing the resistance to extreme high temperature.
- Wide tread, round shoulder and streamlined pattern design providing stable ride, good floating force, excellent steering ability and uniform tread wear.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity (kg) 10km/h/50km/h	Inflation Pressure (kPa) 10km/h/50km/h
11.00-16	6	6.50H	TT/TL	8.0	267 935	2060*1180	245
14.00-20	18	7.50V	TT/TL	9.0	375 1220	4125*2360	245



W-15 E-3

- Applications: mining truck and fuel truck.
- The tire with heavy-duty nylon body and super-tough surface to be best for mining, building and irrigation project applications.
- Extra-deep and wide pattern reducing sliding risk, enhancing stability and increasing traction force.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity (kg) 70km/h	Inflation Pressure (kPa) 70km/h
11.00-20	18	8.00	TT	22.0	293 1085	3835	910
12.00-20	18	8.50	TT	22.0	315 1125	3940	810
	20	8.50	TT	22.0	315 1125	4200	880
14.00-20	20	10.00	TT/TL	20.0	375 1265	5250	770
	28	10.00	TT/TL	20.0	375 1265	5860	900



W-15A E-3

- Applications: mining truck and fuel truck.
- The tire with heavy-duty nylon body and super-tough surface to be best for mining, building and irrigation project applications.
- Extra-deep and wide pattern reducing sliding risk, enhancing stability and increasing traction force.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity (kg) 70km/h	Inflation Pressure (kPa) 70km/h
14.00-20	20	10.00	TT/TL	20.0	375 1265	5250	770
	28	10.00	TT/TL	20.0	375 1265	5860	900
14.00-25	28	10.00W	TT	25.5	375 1370	5600	650
	30	10.00W	TT	25.5	357 1318	6150	750



W-15B E-3

- Applications: mining truck and fuel truck.
- The tire with heavy-duty nylon body and super-tough surface to be best for mining, building and irrigation project applications.
- Extra-deep and wide pattern reducing sliding risk, enhancing stability and increasing traction force.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity (kg) 70km/h	Inflation Pressure (kPa) 70km/h
11.00-20	18	8.50	TT	22.0	293 1085	3835	910



W-15C E-3

- Applications: mining truck and fuel truck.
- The tire with heavy-duty nylon body and super-tough surface to be best for mining, building and irrigation project applications.
- Extra-deep and wide pattern reducing sliding risk, enhancing stability and increasing traction force.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity (kg) 70km/h	Inflation Pressure (kPa) 70km/h
13.00-25	30	8.5/1.3	TT	22.0	350 1300	5125	750
	32	8.5/1.3	TT	22.0	350 1300	5375	800

W-16 E-2

- Applications: MPT and military vehicles, such as tank, armoured car.
- All-terrain tire designed for both on and off road applications.
- The unique pattern and special compound producing highway application and abrasion performance.
- Reinforced carcass assures strength and durability, improving load capacity.



Size	PR	Load Index	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions SW (mm) OD	Load Capacity (kg)	Inflation Pressure (psi)	Max Speed (km/h)
15.00-20	18	160E	12.00	TT	18.0	405 1310	4500	400	70
	20	164E	12.00	TT	18.0	405 1310	5000	550	70
	22	168E	12.00	TT	18.0	405 1310	5600	700	70
15.00-21	12	154F	11.25	TT	18.0	405 1310	3750	475	80
	14	158G	11.25	TT	18.0	405 1310	4250	475	90

W-16A E-2

- Applications: MPT and military vehicles, such as tank, armoured car, as well as grader.
- All-terrain tire designed for both on and off road applications.
- The unique pattern and special compound producing highway application and abrasion performance.
- Reinforced carcass assures strength and durability, improving load capacity.



Size	PR	Load Index	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions SW (mm) OD	Max Load (kg)	Inflation Pressure (psi)	Max Speed (km/h)
12.00-18 (320-457)	8	124J	8.00	TT	23.0	337 1084	1600	300	100
	10	132J	8.00	TT	23.0	337 1084	2000	360	100
	14	136J	8.00	TT	23.0	337 1084	2350	420	100
8.25-20	12	132J	8.50	TT	19.0	235 995	2000	700	100
	14	136J	8.50	TT	19.0	235 995	2240	810	100
9.00-20	10	134E	7.00	TT	20.0	256 1035	2120	560	70
	14	141E	7.00	TT	20.0	256 1035	2575	770	70
	16	145E	7.00	TT	20.0	256 1035	2900	880	70
10.00-20	10	137E	7.50	TT	20.0	280 1075	2300	500	70
	14	144E	7.50	TT	20.0	280 1075	2800	700	70
	16	148E	7.50	TT	20.0	280 1075	3000	810	70
11.00-20	16	148J	8.00	TT	18.5	293 1085	3250	810	90
	18	151J	8.00	TT	18.5	293 1085	3450	880	90
12.00-20	18	154J	8.50	TT	22.0	315 1145	3750	810	100
	20	156J	8.50	TT	22.0	315 1145	4000	890	100
13.00-20	18	156F	10.00	TT	20.0	367 1200	4000	600	90
	20	159F	10.00	TT	20.0	367 1200	4375	700	90
14.00-20	16	153G	10.00	TT	24.0	375 1265	3650	375	90
	18	160G	10.00	TT	24.0	375 1265	4500	670	90
	20	164G	10.00	TT	24.0	375 1265	5000	770	90
	28	169G	10.00	TT	24.0	375 1265	5860	900	90
16.00-24	16	160J	11.25	TT	28.0	430 1495	4500	325	100
	24	171J	11.25	TT	28.0	430 1495	6150	475	100
1300x530-533	12	156B	440x533	TT/TL	24.0	530 1300	4050	400	50
	14	160B	440x533	TT/TL	24.0	530 1300	4500	475	50
	16	162B	440x533	TT/TL	24.0	530 1300	4775	525	50
	20	167B	440x533	TT/TL	24.0	530 1300	5450	570	50

W-16B E-2

- Applications: MPT and military vehicles, such as tank, armoured car.
- All-terrain tire designed for both on and off road applications.
- The unique pattern and special compound producing highway application and abrasion performance.
- Reinforced carcass assures strength and durability, improving load capacity.



Size	PR	Load Index	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions SW (mm) OD	Max Load (kg)	Inflation Pressure (psi)	Max Speed (km/h)
15.5-20	22	168E	12.00	TT	18.0	425 1260	5600	700	70
16.00-20	10	140E	10.00W	TT	22.0	460 1384	2500	250	70
	20	164E	10.00W	TT	22.0	460 1384	5000	500	70
	28	168E	10.00W	TT	22.0	460 1384	5600	625	70
	32	170E	10.00W	TT	22.0	460 1384	6000	675	70
16.00-24 (600-610)	24	178C	13.00	TT/TL	20.0	500 1600	7500	450	60
1200x500-508 (600/70-508)	16	159F	388x508	TT/TL	23.0	500 1200	4375	500	90
1220x400-533 (400/80-21)	10	141G	310x533	TT/TL	23.0	418 1200	2575	320	90
1500x600-635	14	169G	500x635	TT/TL	25.0	600 1500	5750	380	90
	18	173G	500x635	TT/TL	25.0	600 1500	6500	470	90
	22	178G	500x635	TT/TL	25.0	600 1500	7050	550	90
1600x600-685	24	180F	500x685	TT/TL	27.0	600 1600	8000	440	80

W-16C E-2

- Applications: MPT and military vehicles, such as tank, armoured car.
- All-terrain tire designed for both on and off road applications.
- The unique pattern and special compound producing highway application and abrasion performance.
- Reinforced carcass assures strength and durability, improving load capacity.



Size	PR	Load Index	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions SW (mm) OD	Max Load (kg)	Inflation Pressure (psi)	Max Speed (km/h)
16.00-20	28	168E	10.00W	TT	22.0	438 1343	5600	625	70
	32	170E	10.00W	TT	22.0	438 1343	6000	675	70

W-16D E-2

- Specially designed for MPT and military truck, suitable to both on and off road applications.
- Pattern designs deliver excellent traction in all weather conditions.
- Reinforced carcass assures strength and durability, improving load capacity.
- The unique pattern and special compound producing highway application and abrasion performance.



Size	PR	Load Index	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions SW (mm) OD	Max Load (kg)	Inflation Pressure (psi)	Max Speed (km/h)
12.5-20 (335/80-20)	10	131F	11.00	TT/TL	17.0	325 1040	1950	300	80
	12	132G	11.00	TT/TL	17.0	325 1040	2000	425	90
	16	141J	11.00	TT/TL	17.0	325 1040	2575	500	100
	18	149J	11.00	TT/TL	17.0	325 1040	3250	650	100

W-16E E-2

- These are the tires that have been developed for special military land vehicles, for all kinds of pavement conditions.
- The tread pattern is resistant to wear and damage.
- Its powerful nylon body protects the tire and provides long life.



Size	PR	Load Index	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions SW (mm) OD	Max Load (kg)	Inflation Pressure (psi)	Max Speed (km/h)
13.00-18 (340-457)	8	131F	9.00	TT/TL	21.0	354 1125	1950	300	80
	10	135G	9.00	TT/TL	21.0	354 1125	2180	325	90
	18	141G	9.00	TT/TL	21.0	354 1125	2500	480	90

GSE01

- Applications: Ground Support Equipment (GSE) in airport.
- Good all-round bias-ply tire with a shallow saw-tooth ribbed tread pattern for grip and longer tread-life.



Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions SW (mm) OD	Load Capacity (kg) 90km/h	Inflation Pressure (psi) 90km/h
8.00-16.5	8	6.00	TL	13.00	205 720	925	450

GSE02

- Applications: Ground Support Equipment (GSE) in airport.
- Good all-round bias-ply tire with a shallow saw-tooth ribbed tread pattern for grip and longer tread-life.



Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions SW (mm) OD	Load Capacity (kg) 90km/h	Inflation Pressure (psi) 90km/h
7.50-16	14	6.00G	TT	16.0	215 805	1500	770
8.75-16.5	10	6.75	TL	18.0	225 760	1170	520

TRACPRO668

- Radial agri-tires suitable for high-powered tractors, harvesting and combined machines, carrying very high loads at low pressure.
- Large selection of sizes ensuring the perfect fit for your equipment on road and fields, or even difficult and uneven terrain.
- The extensive footprint area allowing even ground pressure distribution and minimizing soil compaction, then making TRACPRO668 also suitable for soil preparation, planting and soil treatments.
- Comparing with the bias, the flexible strong carcass and the wide deep lugs producing minimal rolling resistance, more traction, lower vibration, higher driving comfort and longer life service.
- Maximum resistance to impact and puncturing ensured by the high quality materials used.

Size	Load Index	Rim	Type	Inflated Dimensions SW mm OD	Load Capacity lbs kg	Inflation Pressure psi bar	Max Speed mph km/h	Replacement
250SR20	116A8/116B	W8	TT/TL	249 940	6061 2755	35 2.4	25 40	9.5R20
280SR24	115A8/112B	W10	TL	292 1086	2673 1215	23 1.6	25 40	11.2R24
280SR22	113A8/115B	W10	TL	292 1187	2904 1320	23 1.6	25 40	11.2R28
320SR20	119A8/116B	W11	TL	329 1052	2992 1360	23 1.6	25 40	12.4R20
320SR24	122A8/119B	W11	TL	329 1154	3300 1500	23 1.6	25 40	12.4R24
320SR28	124A8/121B	W11	TL	329 1255	3530 1600	23 1.6	25 40	12.4R28
340SR24	125A8/122B	W12	TL	353 1188	3640 1650	23 1.6	25 40	13.6R24
340SR28	127A8/124B	W12	TL	353 1289	3860 1750	23 1.6	25 40	13.6R28
340SR38	133A8/130B	W12	TL	353 1543	4532 2060	26 1.8	25 40	13.6R38
380SR24	131A8/128B	W13	TL	390 1256	4290 1950	23 1.6	25 40	14.9R24
380SR28	133A8/130B	W13	TL	390 1357	4532 2060	23 1.6	25 40	14.9R28
380SR30	135A8/132B	W13	TL	390 1408	4796 2180	23 1.6	25 40	14.9R30
420SR28	139A8/136B	W15L	TL	438 1425	5360 2430	23 1.6	25 40	16.9R28
420SR30	140A8/137B	W15L	TL	438 1475	5510 2500	23 1.6	25 40	16.9R30
420SR34	142A8/139B	W15L	TL	438 1578	5840 2650	23 1.6	25 40	16.9R34
420SR38	144A8/141B	W15L	TL	438 1679	6175 2800	23 1.6	25 40	16.9R38
460SR30	145A8/142B	W16L	TL	475 1544	6395 2900	23 1.6	25 40	18.4R30
460SR34	147A8/144B	W16L	TL	475 1646	6765 3075	23 1.6	25 40	18.4R34
460SR38	149A8/146B	W16L	TL	475 1747	7165 3250	23 1.6	25 40	18.4R38
520SR38	155A8/152B	DW18L	TL	536 1849	8545 3875	23 1.6	25 40	20.8R38
520SR42	157A8/157B	DW18L	TL	536 1952	9095 4125	23 1.6	25 40	20.8R42
520SR46	158A8/158B	DW18L	TL	536 2045	9350 4250	23 1.6	25 40	20.8R46
650SR38	173D/170E	DW23B	TL	709 2070	14300 6500	35 2.4	40 65	
480SR42	151A8/151B	W16A	TL	495 1850	7610 3450	23 1.6	25 40	18.4R42
480SR46	158A8/158B	W16A	TL	495 1964	9380 4250	35 2.4	25 40	18.4R46
480SR50	150D	DW15B	TL	500 2045	9650 4375	35 2.4	40 65	
4007SR38	138A8/135B	DW14L	TL	395 1565	5200 2360	23 1.6	25 40	15.9R38
6207SR28	168A8	DW20B	TL	633 1590	11686 5300	46 3.2	25 40	23.1R28
6507SR32	172A8	DW20B	TL	662 1817	13891 6300	46 3.2	25 40	24.5R32
6507SR38	169D/165E	DW23B	TL	676 1940	12800 5800	35 2.4	40 65	
7107SR32	177A8	DW23B	TL	735 1850	16095 7300	46 3.2	25 40	
2807R18	114A8/114B	W9	TL	282 849	2596 1180	35 2.4	25 40	
3207R24	116A8/116B	W10	TL	316 1099	2750 1250	23 1.6	25 40	
3607R24	122A8/122B	W11	TL	352 1147	3300 1500	23 1.6	25 40	
3807R24	125A8/125B	W12	TL	370 1193	3640 1650	23 1.6	25 40	
3807R28	127A8/127B	W12	TL	370 1292	3850 1750	23 1.6	25 40	
4207R24	130A8/130B	W13	TL	415 1253	4200 1900	23 1.6	25 40	
4207R28	133D	W13	TL	415 1345	4542 2060	23 1.6	40 65	
4807R28	145D/148A8	W15L	TL	468 1415	6380 2900	35 2.4	40 65	
4807R30	141D	W15L	TL	468 1474	4565 2075	35 2.4	40 65	
4807R34	143A8/143B	W15L	TL	468 1550	6005 2725	23 1.6	25 40	
4807R38	145A8/145B	W15L	TL	468 1684	6380 2900	23 1.6	25 40	
5207R34	148A8/148B	W16L	TL	520 1638	6930 3150	13 1.6	25 40	
5207R38	150D	W16L	TL	520 1740	7370 3350	23 1.6	40 65	
5807R38	155D	W18L	TL	584 1825	8525 3875	23 1.6	40 65	
6007R30	158D/155E	DW18L	TL	605 1608	9370 4250	23 1.6	40 65	
6207R42	166D	DW20B	TL	625 1941	11660 5300	35 2.4	40 65	
7107R38	166D	DW23B	TL	716 1959	11685 5300	23 1.6	40 65	
7107R42	179A8	DW23B	TL	725 2070	17085 7750	46 3.2	25 40	
8007R38	178D/175E	DW25B	TL	810 2065	16500 7500	35 2.4	40 65	
4806R24	133D	DW15L	TL	479 1234	4532 2060	23 1.6	40 65	
4806R28	136D	DW15L	TL	479 1335	4940 2240	23 1.6	40 65	
5406R24	146A8	DW16L	TL	535 1312	6800 3000	35 2.4	25 40	
5406R28	140D	DW16L	TL	535 1312	5500 2500	23 1.6	40 65	
5406SR28	149D/146E	DW16L	TL	530 1413	7150 3250	35 2.4	40 65	
5406SR30	143D	DW16L	TL	530 1464	5995 2725	23 1.6	40 65	
5406SR34	152D/149E	DW16L	TL	530 1566	7825 3550	35 2.4	40 65	
5406SR38	153D/150E	DW16L	TL	516 1709	8030 3650	35 2.4	40 65	
6006SR28	154D/151E	DW18L	TL	590 1481	8250 3750	35 2.4	40 65	
6006SR38	163D	DW18L	TL	590 1745	8075 3650	23 1.6	40 65	
6506SR38	163D/159E	DW20B	TL	645 1811	10750 4875	35 2.4	40 65	
6506SR42	158D	DW20B	TL	645 1913	9350 4250	23 1.6	40 65	
8006SR32	178A8	DW27B	TL	800 1846	16535 7500	46 3.2	25 40	30.5LR32
9006R32	181A8	DW30B	TL	890 1900	18190 8250	46 3.2	25 40	

TRACPRO668 ROW CROP

- Applications: front wheel in Row Crop tractor for cultivation, harvesting and spraying jobs.
- Compared with the bias, the radial design producing much larger load capacity for the modern agricultural machines.
- Lower soil compaction to improve the crop yield.
- Exceptional traction on wet and dry soil.
- Time and fuel saving, improved ride comfort in the field and on the road.

Size	Load Index	Rim	Type	Inflated Dimensions SW mm OD	Load Capacity lbs kg	Inflation Pressure psi bar	Max Speed mph km/h	Replacement
2306R32	128A8/128B	W6	TL	235 1265	3960 1800	58 4.0	25 40	
2706R32	136A8/136B	W9	TL	280 1345	4928 2240	58 4.0	25 40	
2706R38	136D/139A8	W10	TL	284 1410	4928 2240	52 3.6	40 65	11.2R36
2706R38	140A8/140B	W10	TL	285 1480	5500 2500	58 4.0	25 40	
2706R48	144A8/144B	W8	TL	275 1570	6160 2800	58 4.0	25 40	

TRACPRO668 IF

- Tires with IF (Improved Flexion) are designed with a very flexible cheek, allowing for a larger internal volume and when lower tire pressure is created, a larger treadmill is created.
- At the same tire pressure, an IF tire can increase to 20% more load compared to regular tires.
- The larger tread provides lower fuel costs and results in minimum soil densification.
- The carcass construction with a steel belt ensures a uniform distribution of ground pressure, leakage protection and a long life of the tread.

Size	Load Index	Rim	Type	Inflated Dimensions SW mm OD	Load Capacity lbs kg	Inflation Pressure psi bar	Max Speed mph km/h
IF 600/70R30	159D	DW21B	TL	605 1610	9650 4375	23 1.6	40 65
IF 650/65R38	163D	DW23B	TL	645 1840	10750 4875	23 1.6	40 65
IF 800/70R38	184A8	DW27B	TL	780 2050	19800 9000	35 2.4	25 40

FLPRO360 STEEL BELTED

- Application: spreader, trailer and tanker on and off the road.
- Radial flotation and transport tire with resistant structure providing excellent traction and perfect grip even in bends and when maneuvering.
- The tread pattern design featuring excellent self-cleaning properties in all the conditions of use, and reducing soil compaction preserving the value of the crops.

Size	Load Index	Rim	Type	Inflated Dimensions SW mm OD	Load Capacity lbs kg	Inflation Pressure psi bar	Max Speed mph km/h
56060R22.5	161E	AG16.00	TL	554 1245	10175 4625	58 4.0	44 70
60055R26.5	165E	AG20.00	TL	624 1350	11330 5150	58 4.0	44 70
65055R26.5	167E	AG20.00	TL	645 1360	11990 5450	58 4.0	44 70
71045R22.5	165D	AG24.00	TL	727 1210	11330 5150	58 4.0	40 65
71050R26.5	170D	AG24.00	TL	732 1400	13200 6000	58 4.0	40 65
75060R30.5	181D	AG24.00	TL	754 1675	18150 8250	58 4.0	40 65



FLR3 R-3

- Applications: combine harvester, spreader, sugar cane machinery, implement, agricultural trailer, tanker.
- Flat and wide foot print suitable for flotation applications on soft soil, orchards, etc.
- Tread specially designed to give minimum ground disturbance.
- Increased tread depth and strong carcass ensures long life.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity (kg) 40km/h	Inflation Pressure (kPa) 40km/h
23.1-26	12	DW20	TT/TL	28.0	587 1580	3610	170
	14	DW20	TT/TL	28.0	587 1580	3970	200
	16	DW20	TT/TL	28.0	587 1580	4300	230
23.1-30	12	DW20	TL	17.4	587 1683	3450	160
	16	DW20	TL	17.4	587 1683	4570	230
24.5-32	12	DW21	TL	28.0	623 1775	4390	170
	16	DW21	TL	28.0	623 1775	4994	210
28L-26	12	DW25B, DW23B	TL	27.0	714 1560	3785	140
	16	DW25B, DW23B	TL	27.0	714 1560	4605	200
	20	DW25B, DW23B	TL	27.0	714 1560	5315	280
30.5L-32	12	DW27	TL	29.0	750 1790	4210	110
	16	DW27	TL	29.0	750 1790	4745	140
	20	DW27	TL	29.0	750 1790	5370	170



IMPT F-3

- Applications: implement machinery, hay harvester, baler, agri-trailer, multipurpose truck.
- Ideal tires for modern farming, suitable for both on and off-the-road applications.
- Low section tires, offering high load capacity with minimum soil compaction & great transportation properties.
- Optimum tread arc delivering fullest possible footprint.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity (kg) 40km/h	Inflation Pressure (kPa) 40km/h
6.00-16	6	4.0OE	TT/TL	8.0	169 722	560	340
	8	4.0OE	TT/TL	8.0	169 722	875	430
	10	9.00	TL	9.0	264 710	1240	310
10.0/8-12	8	9.00	TL	9.0	264 710	1650	390
	12	9.00	TL	9.0	264 710	2050	490
	16	9.00	TL	9.0	264 710	2525	390
10.0/75-15.3	12	9.00	TL	9.0	264 760	2110	525
	16	9.00	TL	9.0	264 760	2145	410
	18	9.00	TL	9.0	264 760	2575	475
11.580-15.3	12	9.00	TL	10.0	290 845	2760	510
	16	9.00	TL	10.0	290 845	2425	410
	18	9.00	TL	10.0	290 845	2680	450
12.580-15.3	12	9.00	TL	10.0	307 889	2940	475
	16	9.00	TL	10.0	307 889	2850	370
	18	9.00	TL	10.0	307 889	2910	430
12.580-18	12	W9	TL	11.0	307 965	3350	490
	16	W9	TL	11.0	307 965	4000	550
	18	W9	TL	11.0	307 965	4000	550
13.0/65-18	16	11.00	TL	11.0	336 890	2750	490
	18	11.00	TL	11.0	336 890	2945	550



IMPT5 F-3

- Applications: implement machinery, hay harvester, baler, agri-trailer, multipurpose truck.
- Ideal tires for modern farming, suitable for both on and off-the-road applications.
- Low section tires, offering high load capacity with minimum soil compaction & great transportation properties.
- Optimum tread arc delivering fullest possible footprint.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity (kg) 40km/h	Inflation Pressure (kPa) 40km/h
15.0/65-17	10	13.00	TL	12.0	391 850	2120	360
	12	13.00	TL	12.0	391 850	2360	420
	14	13.00	TL	12.0	391 850	2575	490
	18	13.00	TL	12.0	391 850	3250	650



IMPT7 F-3

- Applications: implement machinery, hay harvester, baler, agri-trailer, multipurpose truck.
- Ideal tires for modern farming, suitable for both on and off-the-road applications.
- Low section tires, offering high load capacity with minimum soil compaction & great transportation properties.
- Optimum tread arc delivering fullest possible footprint.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity (kg) 40km/h	Inflation Pressure (kPa) 40km/h
19.0/45-17	10	16.00	TL	12.0	491 866	2360	300
	14	16.00	TL	12.0	491 866	2800	390
	18	16.00	TL	12.0	491 866	4000	450
500/50-17	10	16.00	TL	12.0	500 945	2800	270
	14	16.00	TL	12.0	500 945	3650	380
	16	16.00	TL	12.0	500 945	3875	440
400/60-15.5	10	AG13.00	TL	12.0	400 945	2240	360
	14	AG13.00	TL	12.0	400 945	2725	490
	18	AG13.00	TL	12.0	400 875	3450	600



SC13 I-3

- Applications: agricultural implement & trailer, sugar cane harvester, spreader, both on and off-the-road.
- Flotation implement design for high load capacities at low inflation pressures, minimising soil compaction and preventing damage to crops.

Size	PR	Load Index	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity (kg) 40km/h	Inflation Pressure (kPa) 40km/h	Max Speed (km/h)
400/60-15.5	14	149A8	13.00	TL	25.0	404 875	3725	200	40
	16	158D	11.75	TL	21.0	400 1070	4250	450	65
	18	164D	11.75	TL	21.0	400 1070	5000	510	65
600/50-22.5	16	165A8	20.00	TL	25.0	600 1170	5150	260	40
	18	168A8	20.00	TL	25.0	600 1170	5500	300	40
	20	168A8	AG24.00	TL	26.0	700 1360	4500	120	40
700/50-26.5	12	169A8	AG24.00	TL	26.0	700 1360	5800	180	40
	16	174A8	AG24.00	TL	26.0	700 1360	6700	240	40
	18	182A8	AG24.00	TL	25.0	750 1670	8500	220	40



FORESTRY LS-2

- Application: logging skidder machines
- Steel belted construction with heavy duty nylon casing giving puncture proof performance & longer tire life.
- Robust lug design with optimum angle & wider width providing excellent traction.
- Specially designed cut resistance tread compound providing excellent cut & chip resistance under severe terrain conditions.
- Thicker sidewall, stronger bead & rim guard protecting from external damages.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity (kg) 30km/h	Inflation Pressure (kPa) 30km/h
16.9-30	10	W15L	TT/TL	48.0	210 1510	2575	210
	16	W15L	TT/TL	48.0	210 1510	3210	300
18.4-26	10	DW16A	TT/TL	50.0	465 1475	2575	170
	16	DW16A	TT/TL	50.0	465 1475	3500	280
18.4-30	10	DW16A	TT/TL	50.0	465 1575	2725	170
	16	DW16A	TT/TL	50.0	465 1575	3500	280
18.4-34	12	DW16A	TT/TL	50.0	465 1680	3250	210
	16	DW16A	TT/TL	50.0	465 1680	3700	280
23.1-26	14	DW20A	TT/TL	53.0	590 1630	4125	210
	16	DW20A	TT/TL	53.0	590 1630	4450	240
24.5-32	16	DH21	TT/TL	55.0	625 1830	5000	210
	20	DH21	TT/TL	55.0	625 1830	5800	280
28L-26	18	DW25A	TT/TL	55.0	715 1645	4800	210
	20	DW25A	TT/TL	55.0	715 1645	5150	240
30.5L-32	18	DH27	TT/TL	55.0	775 1845	5950	210
	20	DH27	TT/TL	55.0	775 1845	6530	240
DH35L-32	26	DH32	TT/TL	58.0	905 2004	7100	280
	26	DH32	TT/TL	58.0	905 2004	8750	240
73x44.00-32	16	DH36	TL	67.0	1153 1870	6900	280
	20	DH36	TL	67.0	1153 1870	8000	340



FOREST MASTER LS-2

- Applications: forestry harvester, forwarder and heavy logging loader.
- Strong carcass with steel belted producing the best resistance to puncture.
- New lug design and wide tread design giving superior traction.
- Perfect design on the tread bars and shoulder offering good self cleaning, side slipage-proof, lateral grip and puncture.
- The reinforced bead and shoulder area coupled with unique tread compound for the excellent service and longer life.

Size	PR	Load Index	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity _{kg} 40km/h	Inflation Pressure _{psi} 40km/h
60050-22.5	20	159A8/167A2	AG 20.00	TT/TL	42	600 1170	4375	550
65045-22.5	20	154A8/161A2	AG 20.00	TT/TL	45	635 1153	3750	500
71040-22.5	20	161A8/168A2	AG 24.00	TT/TL	42	710 1170	4625	550
(70045-22.5)								
71040-24.5	20	163A8/170A2	AG 24.00	TT/TL	48	710 1230	4875	550
50060-26.5	20	165A8/175A2	AG 16.00	TT/TL	53	485 1265	5150	500
60055-26.5	20	165A8/175A2	AG 20.00	TT/TL	48	601 1340	5150	550
71045-26.5	20	168A8/175A2	AG 24.00	TT/TL	48	710 1340	5600	550
(70050-26.5)								
73055-28.5	24	182A8/189A2	AG 24.00	TT/TL	49	750 1485	8500	600
80040-28.5	20	170A8/177A2	AG 28.00	TT/TL	48	800 1340	6000	550
71055-28.5	24	180A8/187A2	AG 24.00	TT/TL	49	710 1525	8000	600
78050-28.5	24	182A8/190A2	AG 26.00	TT/TL	49	780 1525	8500	600



QZ-502

- Applications: tractor front, loader front, mower front.
- Strong nylon carcass ensuring good performance.
- Three-ribs front wheel tires, designed for easy steering.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity _{kg} 40km/h	Inflation Pressure _{psi} 40km/h
650-20	8	5.00F	TT	16.0	180 860	865	420



QZ-602 F-2

- Applications: tractor front for field operations and regular transportation.
- Self-cleaning tread for positive steering.
- Sturdy shoulder board offering excellent sidewall protection.
- Wide tread area ensuring longer life.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity _{kg} 30km/h	Inflation Pressure _{psi} 30km/h
4.00-16	4	3.00D	TT	14.0	110 640	280	320
	6	3.00D	TT	14.0	110 640	300	340
4.50-16	6	3.00D	TT	14.0	122 655	462	450
5.00-15	6	4.00J	TT	14.0	140 665	465	420
5.00-16	6	4.00E	TT	15.0	130 655	550	420
5.50-16	6	4.00E	TT	15.0	150 710	525	370
6.00-16	6	4.00E	TT	15.0	160 740	560	340
6.50-16	6	4.50E	TT	16.0	175 760	615	310
6.50-20	8	5.00F	TT	16.0	180 860	865	420
7.50-16	8	5.50F	TT	20.0	205 810	870	370



QZ-701 R-2

- Applications: tractor for soil tillage and spreading in wet soft fields, such as paddy and shattercane.
- Offering superior grip and enhanced self-cleaning features.
- Tread and sidewall rubber compounds fight off acid and ozone, producing long-life service.
- Strong casing for excellent stability and safety to the operator.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity _{kg} 40km/h	Inflation Pressure _{psi} 40km/h
112-24	8	W10	TT/TL	63.5	285 1105	1225	240
124-24	8	W11	TT/TL	67.0	315 1192	1415	230
124-38	8	W11	TT/TL	67.0	315 1500	1750	230
138-38	8	W12	TT/TL	70.0	345 1600	1910	210
149-24	8	W13	TT/TL	73.0	380 1305	1780	180
169-30	10	W15L	TT/TL	76.0	430 1530	2455	200
169-34	10	W15L	TT/TL	76.0	430 1600	2605	200
184-30	10	W16L	TT/TL	81.0	467 1570	2815	180
184-34	10	W16L	TT/TL	81.0	467 1702	2990	180
184-38	10	W16L	TT/TL	81.0	467 1775	3165	180
198-24	12	DW16	TT/TL	76.0	495 1357	2145	210
208-38	10	W18L	TT/TL	85.0	530 1855	3475	160
208-42	14	W18A	TT/TL	85.0	528 1988	4500	200
231-26	12	DW20	TT/TL	89.0	587 1662	3610	170
231-30	14	DW20	TT/TL	89.0	587 1770	4210	200
231-34	14	DW21	TT/TL	89.0	587 1870	4450	200
245-32	10	DW21	TT/TL	89.0	623 1832	3570	138
281-26	14	DW25	TT/TL	89.0	715 1672	4250	170



QZ-701A R-2

- Applications: tractor for soil tillage and spreading in wet soft fields, such as paddy and shattercane.
- Extra deep tread specially designed to get excellent traction on wet and sticky soil with excellent self-cleaning properties, preventing mud clogging between the lugs.
- Sidewall rubber preventing weather cracking.
- Tough tread compound to resist fast wear.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity _{kg} 40km/h	Inflation Pressure _{psi} 40km/h
650-16	8	4.50E	TT	65.0	165 830	665	250
750-16	8	5.50F	TT	75.0	195 890	750	250
83-20	8	W7	TT	75.0	210 950	790	270
83-24	8	W7	TT	75.0	210 1050	910	270
95-24	10	W8	TT	75.0	240 1150	1210	320
112-24	10	W10	TT	80.0	285 1205	1380	320
124/11-28	10	W10	TT	85.0	285 1255	1495	280
124-28	10	W11	TT	85.0	315 1315	1745	280
11-32	10	W10	TT	87.0	305 1460	1080	160



QZ-702B R-1W

- Applications: tractors in soil tillage operations.
- R-1W pattern ideal for wet and moist soil because of the outstanding self-cleaning properties.
- Extra deep tread lugs as much as 25% deeper than conventional R-1 tyres.
- Also in the harshest operating conditions, excellent traction and extraordinary durability produced.

Size	PR	Load Index	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity _{kg} 30km/h	Inflation Pressure _{psi} 30km/h
95-18	8	105A6	W6	TT	44.5	241 900	915	300



QZ-702 R-1

- Applications: tractor, trailer, harvester, spreader, excavator, soil tillage and spraying machines.
- Large selection of sizes ensures the perfect fit for your equipment.
- Dual angled lugs bracing for better traction, more stability and less squirm.
- Dual rubber compounds — flexible rubber on the sidewalls to resist weather cracking plus super-tough rubber on the tread for long wear.
- Bead-and-rim flange protector reducing downtime by keeping out debris.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions SW OD	Load Capacity kg	Inflation Pressure PSI
500-12	4	3.50-B	TT	22.0	145 590	280	200
600-12	6	4.50-B	TT	22.0	165 640	405	250
600-16	6	4.50-E	TT	22.0	165 745	495	250
750-16	8	5.50-F	TT	20.0	205 810	700	240
550-17	8	4.00-E	TT	22.0	165 745	440	250
750-20	8	5.50-F	TT	24.0	205 910	880	280
83-20	6	W7	TT	30.0	210 895	695	240
	8	W7	TT	30.0	210 895	810	280
83-24	8	W7	TT	30.0	210 995	920	280
95-20	8	W8	TT	33.0	240 950	955	280
95-24	8	W8	TT	30.0	240 1050	1110	280
112-24	8	W10	TT	33.0	285 1105	1225	240
112-28	8	W10	TT	33.0	285 1205	1325	240
	10	W10	TT	33.0	285 1205	1500	300
	12	W10	TT	33.0	285 1205	1675	360
12-38	8	DW11	TT	35.0	330 1575	1570	140
	10	DW11	TT	35.0	330 1575	1800	220
124-24	6	W11	TT	38.0	315 1160	1200	170
	8	W11	TT	38.0	315 1160	1415	230
	10	W11	TT	38.0	315 1160	1630	280
124-28	8	W11	TT	38.0	315 1260	1510	230
	10	W11	TT	38.0	315 1260	1745	280
124-38	8	W11	TT	38.0	315 1565	1750	230
	10	W11	TT	38.0	315 1565	2020	280
136-24	8	W12	TT	37.0	345 1210	1545	210
	10	W12	TT	37.0	345 1210	1790	250
136-28	8	W12	TT	38.0	345 1310	1500	190
	10	W12	TT	38.0	345 1310	1910	250
136-38	8	W12	TT	36.0	345 1565	1900	210
	10	W12	TT	36.0	345 1565	2215	250
149-24	8	W13	TT	35.0	378 1265	1760	180
	10	W13	TT	35.0	378 1265	1990	230
149-26	8	W 13	TT/TL	39.0	378 1315	1820	180
	10	W 13	TT/TL	39.0	378 1315	2050	230
149-28	8	W13	TT/TL	38.0	380 1365	1880	180
	10	W13	TT/TL	38.0	380 1365	2120	230
169-24	10	W15L	TT/TL	39.0	430 1335	2230	200
	12	W15L	TT/TL	39.0	430 1335	2360	260
169-26	10	W15L	TT/TL	39.0	430 1410	2300	200
	12	W15L	TT/TL	39.0	430 1410	2450	260
169-28	10	W15L	TT/TL	39.0	430 1435	2390	200
	12	W15L	TT/TL	39.0	430 1435	2655	260
169-30	10	W15L	TT/TL	40.0	430 1485	2455	200
	12	W15L	TT/TL	40.0	430 1485	2730	240
169-34	8	W15L	TT/TL	39.0	430 1585	2380	170
	10	W15L	TT/TL	39.0	430 1585	2605	200
	12	W15L	TT/TL	39.0	430 1585	2820	230
169-38	8	W15L	TT/TL	39.0	430 1685	2520	170
	10	W15L	TT/TL	39.0	430 1685	2700	200
	12	W15L	TT/TL	39.0	430 1685	2880	230
184-26	10	DW16	TT/TL	38.0	467 1450	2645	180
	12	DW16	TT/TL	38.0	467 1450	2985	230
184-28	8	W16L	TT/TL	38.0	467 1500	2130	140
	10	W16L	TT/TL	38.0	467 1500	2750	180
	12	W16L	TT/TL	38.0	467 1500	3135	220
184-30	8	W16L	TT/TL	38.0	467 1550	2415	140
	10	W16L	TT/TL	38.0	467 1550	2815	180
	12	W16L	TT/TL	38.0	467 1550	3180	230
184-34	8	W16L	TT/TL	38.0	467 1655	2565	140
	10	W16L	TT/TL	38.0	467 1655	2990	180
	12	W16L	TT/TL	38.0	467 1655	3375	230
184-38	10	W16L	TT/TL	41.0	467 1755	3165	180
	12	W16L	TT/TL	41.0	467 1755	3575	230
208-38	10	W18L	TT/TL	42.0	530 1835	3475	160
	12	W18L	TT/TL	42.0	530 1835	4000	200
231-30	12	DW20	TT/TL	42.0	587 1705	3850	170
	16	DW20	TT/TL	42.0	587 1705	4570	230
245-32	12	DW21	TT/TL	42.0	622 1805	4390	170
	16	DW21	TT/TL	43.0	622 1805	4994	210
28L-26	14	DW25A	TT/TL	42.0	715 1615	4250	170
	16	DW25A	TT/TL	42.0	715 1615	4605	200



QZ-702A R-1/HF-2

- Applications: combine harvester, high-power tractor, monster truck.
- High flotation capability along with low soil compaction and excellent traction in the field.
- High load capacity to improve modern farmers' requirements in terms of productivity.
- Flexible sidewall rubber compounded with super-tough tread rubber for superior ride, snag resistance and long wear.
- Bead-and-rim flange protector reducing downtime by keeping out debris.
- Compared with QZ-702, more intensive lugs producing larger traction.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions SW OD	Load Capacity kg	Inflation Pressure PSI	Max Speed (km/h)
231-30	12	DW20	TT/TL	40.0	587 1705	3850	170	30
	16	DW20	TT/TL	40.0	587 1705	4570	230	30
245-32	12	DW21	TT/TL	40.0	622 1805	4390	170	30
	16	DW21	TT/TL	40.0	622 1805	4994	210	30
30.9L-32	16	DH27	TT/TL	50.0	775 1820	4745	140	30
	18	DH27	TT/TL	50.0	775 1820	5370	170	30
	20	DH27	TT/TL	50.0	775 1820	5950	210	30
66x43.00-25	10	36.00	TL	38.0	1054 1702	4500	170	40
	12	36.00	TL	38.0	1054 1702	5000	210	40
	16	36.00	TL	38.0	1054 1702	6100	290	40



QZ-702C R-1/HF-2

- Applications: high-powered tractor, and monster truck.
- The high flotation agricultural tires, large ground contact area, low-pressure ratio on the ground and less damage to soil and sapling.
- Tread bars of certain angle give good self-cleaning action, excellent traction and side slippage-proof.
- Deep tread design and cut-resistant tread compound give extended service life.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions SW OD	Load Capacity kg	Inflation Pressure PSI
66x43.00-25	10	36.00	TL	38.0	1054 1702	4500	170
	12	36.00	TL	38.0	1054 1702	5000	210
	16	36.00	TL	38.0	1054 1702	6100	290



QZ-702N R-1

- Applications: tractor, harvester, spreader.
- More intensive lugs providing better traction, self-cleaning properties and stability.
- The ideal partner used even on the harshest ground conditions.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions SW OD	Load Capacity kg	Inflation Pressure PSI
18-42	12	W16L	TT/TL	40.0	467 1857	3000	180
208-42	12	W18L	TT/TL	42.0	528 1935	3350	150
231-34	10	DW20B, DW20	TT/TL	42.0	602 1799	2900	110
	12	DW20B, DW20	TT/TL	42.0	602 1799	3350	150



QZ-703

- Applications: agricultural implement, tractor trailer, spreader, harvester.
- Designed especially for agricultural machines with load capacity 9-12 tons.
- Tough nylon-cord body for durability and long wear.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions SW OD	Load Capacity kg	Inflation Pressure PSI
15.505-18	12	W13	TT	15.0	395 980	2890	310
16.9/70-18	14	W13	TT	15.0	425 1065	3650	410

QZ-704 F-2

- Applications: 2WD tractor front in soil tillage applications.
- Particularly suitable for all operations requiring a high level of handling.
- Providing high flotation capability contributing to reduce soil compaction.



Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity μ g 30km/h	Inflation Pressure μ psi 30km/h
11L-15	8	8.00	TT/TL	21.0	280 810	950	300
1000-16	10	W8L	TT/TL	16.0	275 910	1325	340
1100-16	10	W10L	TT/TL	16.0	315 970	1350	345
14L-16.1	12	16.1x11LB	TT/TL	35.0	355 985	1940	340
	16	16.1x11LB	TT/TL	35.0	355 985	2330	500

QZ-705 R-1

- Applications: tractor, harvester, spreader.
- Ideal for use on soft soil, chards and similar applications.
- Specially engineered tread design providing high flotation.
- Increased tread depth and strong carcass ensuring good stability, traction, self-cleaning properties and long service life.



Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity μ g 30km/h	Inflation Pressure μ psi 30km/h
23.1-26	12	DW20	TT/TL	34.0	587 1605	3610	170
	14	DW20	TT/TL	34.0	587 1605	3970	200
	16	DW20	TT/TL	34.0	587 1605	4300	230

QZ-706 I-1

- Applications: 2WD tractor front in soil tillage and transport applications.
- This tire ensuring a high level of handling comfort.
- Available in different versions to specifically meet end-user requirements in terms of cut and chip resistance and heavy-duty service.



Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity μ g 30km/h	Inflation Pressure μ psi 30km/h
900-16	10	6.00F	TT	12.0	235 850	1445	325
1000-16	10	6.00F	TT	12.0	276 894	1650	320

QZ-707 R-1

- Applications: pivot irrigator.
- Round-shaped lugs to reduce soil damage and protect the precious crops.
- Flexible sidewall dual rubber compounds combined with super-tough tread rubber for long wear and resistance to weather checking.



Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity μ g 40km/h	Inflation Pressure μ psi 40km/h
11.2-38	4	W10	TT/TL	30.0	285 1465	950	120

QZ-708 R-1

- Applications: pivot irrigator.
- Round-shaped lugs to reduce soil damage and protect the precious crops.
- Flexible sidewall dual rubber compounds combined with super-tough tread rubber for long wear and resistance to weather checking.



Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity μ g 40km/h	Inflation Pressure μ psi 40km/h
11.2-24	4	W10	TT/TL	28.0	285 1105	845	130
	6	W10	TT/TL	28.0	285 1105	1045	180
	8	W10	TT/TL	28.0	285 1105	1225	240
14.9-24	4	W13	TT/TL	30.5	378 1265	1210	100
	6	W13	TT/TL	30.5	378 1265	1510	140
	8	W13	TT/TL	30.5	378 1265	1760	180

QZ-709 I-1

- Applications: harvesting machines, hay baler, bale rack, seeder, windrower, and fertilizer/manure spreader on and off-the-road services.
- Multi rib, low section I-1 tires designed to provide high flotation with minimum soil compaction with excellent load distribution.
- Cut-resistant sidewall reducing downtime, shock-fortified nylon-cord body resisting impacts.
- Specially fortified rubber resisting stubble puncture and tire erosion, and stubble stomper construction available in certain sizes.



Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	IMP@40km/h Max Load(kg) Inflation Pressure(kpa)	SL IMP@65km/h Max Load(kg) Inflation Pressure(kpa)
400-18	4	3.00D	TT/TL	4.5	112 670	460 275	460 275
500-15	4	3.00D	TT/TL	5.5	130 640	430 225	430 225
590-15	4	4.50E	TT/TL	6.0	155 665	515 250	515 250
600-16	6	4.00E	TT/TL	6.5	158 710	685 275	685 275
640-15	6	4.5K	TT/TL	6.5	163 685	670 275	670 275
650-16	6	4.50E	TT/TL	7.0	173 735	775 275	775 275
670-15	4	4.5K	TT/TL	6.5	170 705	545 195	545 195
	6	4.5K	TT/TL	6.5	170 705	730 275	730 275
750-14	4	5.50F	TT/TL	7.5	194 686	615 190	615 190
	6	5.50F	TT/TL	7.5	194 686	805 275	805 275
750-16	8	5.50F	TT/TL	6.5	203 808	1100 325	1100 325
760-15	8	5.50	TT/TL	6.5	200 721	950 360	950 360
750-20	4	5.50F	TT/TL	7.5	203 855	775 150	775 150
	6	5.50F	TT/TL	7.5	203 855	980 225	980 225
	8	5.50F	TT/TL	7.5	203 855	1185 300	1185 300
900-10	4	6LB	TT/TL	8.5	235 696	670 170	670 170
	8	6LB	TT/TL	8.5	235 696	860 225	860 225
	12	6LB	TT/TL	8.5	235 696	1070 300	1070 300
900-16	8	6LB	TT/TL	8.5	235 850	1315 275	1315 275
	12	6LB	TT/TL	8.5	235 850	1445 300	1445 300
900-24	8	W8	TT/TL	8.5	272 1095	1590 250	1590 250
	12	W8	TT/TL	8.5	272 1095	1900 300	1900 300
1000-15	8	8LB	TT/TL	9.0	276 855	1425 240	1425 240
	12	8LB	TT/TL	9.0	276 855	1550 300	1550 300
10580-18	10	W9-18	TT	6.5	276 885	1950 370	1950 370
	12	W9-18	TT	6.5	276 885	2175 410	2175 410
11.25-24	8	W10	TT/TL	9.5	325 1170	1860 200	1860 200
	12	W10	TT/TL	9.5	325 1170	2360 330	2360 330
11.25-28	8	W10	TT/TL	9.5	325 1275	1925 200	1925 200
	12	W10	TT/TL	9.5	325 1275	2430 330	2430 330
8.5L-14	6	6KB	TT/TL	9.0	215 720	850 220	850 220
	8	6KB	TT/TL	9.0	215 720	1020 300	1020 300
9.5L-14	8	8.00	TT/TL	6.0	239 737	1050 280	1050 280
	12	8.00	TT/TL	6.0	239 737	1360 360	1360 360
9.5L-15	8	8LB	TT/TL	6.0	240 765	1100 280	1100 280
	12	8LB	TT/TL	6.0	240 765	1510 360	1510 360
11L-14	8	8K	TT/TL	6.0	280 752	1080 220	1080 220
	12	8K	TT/TL	6.0	280 752	1390 330	1390 330
11L-15	8	W8L	TT/TL	6.0	280 775	1130 220	1130 220
	12	W8L	TT/TL	6.0	280 775	1465 330	1465 330
11L-16	8	W8L	TT/TL	6.0	275 800	1175 220	1175 220
	12	W8L	TT/TL	6.0	275 800	1505 330	1505 330
12.5L-15	12	10.00	TT/TL	6.0	317 825	1745 330	1745 330
	16	10.00	TT/TL	6.0	317 825	2165 390	2165 390
12.5L-16	12	10.00	TL	10.0	317 850	1800 330	1800 330
	16	10.00	TL	10.0	317 850	2220 390	2220 390

QZ-709A I-1

- Applications: free-rolling wheels used in harvesting machines, hay baler, bale rack, seeder, windrower, and fertilizer/manure spreader.
- Multi rib, low section I-1 tires designed to provide high flotation with minimum soil compaction with excellent load distribution.
- Cut-resistant sidewall reducing downtime, shock-fortified nylon-cord body resisting impacts.
- Specially fortified rubber resisting stubble puncture and tire erosion, and stubble stomper construction available in certain sizes.



Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm) SW OD	Load Capacity μ g 40km/h	Inflation Pressure μ psi 40km/h
900-16	10	6.00	TT	9.0	234 845	1480	360
2000-145(248-145)	10	AG 6.75	TT/TL	9.0	210 1785	1050	500
	14	AG 6.75	TT/TL	9.0	210 1785	1150	700
120-18(40-18)	16	11.00	TL	8.0	342 2688	3670	700

QZ-709B I-1

- Applications: harvesting machines, hay baler, bale rack, seeder, windrower, and fertilizer/manure spreader on and off-the-road services.
- Multi rib, low section I-1 tires designed to provide high flotation with minimum soil compaction with excellent load distribution.
- Specially fortified rubber resisting stubble puncture and tire erosion, and stubble stomper construction available in certain sizes.
- Compared with QZ-709, reinforced cut-resistant sidewall reducing downtime, shock-fortified nylon-cord body resisting impacts.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm)		IMP@40km/h		SLIMP@65km/h	
					SW	OD	Max Load(kg)	Inflation Pressure(kpa)	Max Load(kg)	Inflation Pressure(kpa)
12.5L-15	10	10.00	TL	6.0	317	780	1535	280	1230	280
	12	10.00	TL	6.0	317	780	1745	330	1395	330
	16	10.00	TL	6.0	317	780	2165	390	1730	420

QZ-709M I-1

- Applications: tank, wagon and trailer for on and off-the-road services, as well as the steer tires on combine-harvester.
- Multi rib, low section I-1 tires designed to provide high flotation with minimum soil compaction with excellent load distribution.
- Cut-resistant sidewall reducing downtime, shock-fortified nylon-cord body resisting impacts.
- Specially fortified rubber resisting stubble puncture and tire erosion, and stubble stomper construction available in certain sizes.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm)	IMP @40km/h	SL IMP @65km/h
					SW OD	Max Load(kg) Inflation Pressure(kpa)	Max Load(kg) Inflation Pressure(kpa)
14L-16.1	8	16.1x11LB	TT/TL	10.0	355 940	1575 170	1575 170
	12	16.1x11LB	TT/TL	10.0	355 940	2090 280	2090 280
	14	16.1x11LB	TT/TL	10.0	355 940	2345 330	2345 330
	18	16.1x11LB	TT/TL	10.0	355 940	2855 410	2855 410
16.5L-16.1	10	16.1x14LB	TT/TL	11.0	420 1025	2360 220	2360 220
	14	16.1x14LB	TT/TL	11.0	420 1025	2900 300	2900 300
	18	16.1x14LB	TT/TL	11.0	420 1025	3330 360	3330 360
	20	16.1x14LB	TT/TL	11.0	420 1025	3500 410	3500 410
19L-16.1	10	16.1x16LB	TT/TL	12.0	483 1085	2725 190	2725 190
	14	16.1x16LB	TT/TL	12.0	483 1085	3175 250	3175 250
	18	16.1x16LB	TT/TL	12.0	483 1085	3625 300	3625 300
	20	16.1x16LB	TT/TL	12.0	483 1085	3850 330	3850 330
21.5L-16.1	10	16.1x18LB	TT/TL	14.0	545 1130	3000 170	3000 170
	14	16.1x18LB	TT/TL	14.0	545 1130	3550 220	3550 220
	18	16.1x18LB	TT/TL	14.0	545 1130	4000 300	4000 300
	20	16.1x18LB	TT/TL	14.0	545 1130	4300 330	4300 330
49-17	20	13.00	TT/TL	11.0	425 1200	3000 375	3000 375
	24	13.00	TT/TL	11.0	425 1200	3300 385	3300 385
	28	13.00	TT/TL	11.0	425 1200	3600 400	3600 400

QZ-710 R-1

- Applications: tractor, harvester, spreader.
- Strong casing to carry heavy loads.
- Dual angled lugs to give better traction in the field and provide comfortable ride on road.
- More tensile lugs providing uniform destruction of load.
- Optimum tread depth and special tread compound for higher mileage.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm)	Load Capacity @40km/h	Inflation Pressure @40km/h
					SW OD	40km/h	40km/h
11.2-20	8	W10	TT	36.0	285 1005	1085	240
15.5-38	8	W14L	TT	38.0	395 1570	2060	180
28.1-26	12	DW25	TT	46.0	750 1750	4200	170

QZ-711 R-1

- Applications: front wheel in Row Crop tractor for cultivation, harvesting and spraying jobs.
- Round shoulder design for soil and crop protection.
- Optimum lug shapes and angles provide an excellent grip.
- Durable tread rubber compound guaranteeing long lifetime.

Size	PR	Rim	Tube Type	Tread Depth (mm)	Inflated Dimensions (mm)	Load Capacity @40km/h	Inflation Pressure @40km/h
					SW OD	40km/h	40km/h
9.5-32	8	W8	TT	28.0	240 1250	1260	280

PNLMAX

- Applications: loader & earthmover used in the harsh conditions, such as contraction and mining areas.
- Super strong solid OTR tire improving load capacity and resistance to puncture, extend service life.
- Special colloidal anti-static formula to do the effective elimination of static accumulation, improving the safety of the workplace and personnel.

Size	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load capacity(kg)				Other Vehicles (kg)	Weight
					10km/h	16km/h	26km/h	16km/h		
					Loading Rotation	Loading Rotation	Loading Rotation	16km/h		
14.00-20	E-4	8.00	321	1220	11200	8800	8900	8650	8500	326.0
14.00-24	E-4	10.00	328	1329	12780	10210	12320	9240	11460	416.0
17.5-25	E-4	14.00	396	1310	17720	14180	16880	12690	15960	448.0
20.5-25	E-4	15.00	485	1350	21200	16960	20480	15400	19100	743.0
23.5-25	E-4	19.50	527	1540	30830	24660	29790	22400	27770	2080.0
26.5-25	L-5	22.00	650	1735	39300	31400	37400	28100	35400	2710.0

POSTR&POSSM

- Applications: lifter or forklift in tough working conditions.
- Super strong press-on band solid tire with special compounds improving load capacity and resistance to puncture, extend service life.
- Special colloidal anti-static formula to do the effective elimination of static accumulation, improving the safety of the workplace and personnel.

Size (inch)	Size (mm)	Load capacity(Kg)		Balance forklift		Other Forklifts
		10km/h	16km/h	10km/h	16km/h	16km/h
		Drive	Steer	Drive	Steer	
10*5*61/4	254*127*158.8	1292	1156	1238	1142	993
10*5*61/2	254*127*165.1	1278	1142	1224	1129	986
101/2*6*5	267*152*127	1761	1564	1686	1564	1360
131/2*51/2*8	343*140*203.2	1904	1700	1822	1686	1469
14*5*10	356*127*254	1680	1518	1616	1506	1242
14*41/2*8	356*114*203.2	1482	1318	1414	1306	1142
15*5*111/4	381*127*285.8	3415	3035	2905	3075	2390
15*6*111/4	381*152*285.8	3875	3955	3305	3420	2720
15*7*111/4	381*176*285.8	4325	4335	3715	3755	3040
15*8*111/4	381*203*285.8	4775	4560	4125	4090	3360
151/2*5*10	394*127*254	1470	1210	1315	1100	1050
151/2*6*10	394*152*254	1870	1530	1665	1400	1330
16*41/2*12	406*127*305	1890	1660	1742	1560	1400
16*5*101/2	406*127*266.7	1400	1250	1340	1240	1080
16*6*101/2	406*152*266.7	1780	1580	1700	1570	1370
16*7*101/2	406*178*266.7	2325	1910	2070	1740	1660
161/4*5*111/4	413*127*285.8	1530	1250	1360	1145	1090
161/4*6*111/4	413*152*285.8	1920	1580	1715	1440	1370
18*5*121/8	457*127*308	2081	1850	1986	1836	1591
18*6*121/8	457*152*308	2652	2366	2339	2040	2040
18*7*121/8	457*178*308	3223	2870	3087	2856	2475
18*8*121/8	457*203*308	2780	2480	2670	2470	2150
18*9*121/8	457*229*308	4372	3890	4175	3862	3359
21*7*15	533*178*381	2670	2380	2550	2360	2050
21*8*15	533*203*381	4270	3801	4080	3781	3291
21*9*15	533*229*381	4923	4379	4706	4352	3794
22*7*16	559*178*406.4	2975	2450	2650	2230	2125
22*8*19	559*203*406.4	4434	3944	4230	3917	3407
22*9*16	559*229*406.4	5100	4542	4882	4515	3930
22*10*16	559*254*406.4	5780	5141	5522	5114	4447
22*12*16	559*305*406.4	7120	6338	6800	6297	5481
28*12*22	711*305*558.8	8527	7589	8146	7548	6562

PNSH01-W/PNSH01

- Applications: lifter or forklift in tough working conditions.
- Super strong pneumatic solid tire improving load capacity and resistance to puncture, extend service life.
- Special colloidal anti-static formula to do the effective elimination of static accumulation, improving the safety of the workplace and personnel.
- PNSH01-W tires with light-colored rubber formula to eliminate the marking issue on the ground to avoid polluting the operating environment.

Size	Rim	Section Width (mm)	Overall Diameter (mm)	Load capacity(kg)		Balance forklift				Other Forklifts (kg)	Weight kg
				10km/h		16km/h		26km/h			
				Drive	Steer	Drive	Steer	Drive	Steer		
4.00-8	3.00	115	423	1055	845	1020	765	950	715	730	12.2
	3.75	115	423	1050	845	1020	765	950	715	730	
5.00-8	3.00	126	469	1210	970	1175	880	1095	820	840	18.0
	4.00	140	545	1925	1535	1855	1390	1730	1295	1325	
6.50-10	5.00	157	597	2840	2110	2545	1910	2370	1780	1820	36.6
7.00-9	5.00	170	578	2370	2015	2805	1925	2370	1750	1785	32.2
7.00-12	5.00	168	683	3015	2410	2910	2185	2710	2035	2075	45.0
7.00-15	5.50	178	759	3590	2870	3465	2600	3225	2420	2475	68.8
	6.00	178	759	3590	2870	3465	2600	3225	2420	2475	
7.50-15	6.00	215	774	3690	2950	3425	2570	3190	2395	2450	68.8
	6.50	215	774	3690	2950	3425	2570	3190	2395	2450	
7.50-16	5.50	181	819	3910	3130	3780	2835	3520	2640	2700	75.4
	6.00	181	819	3910	3130	3780	2835	3520	2640	2700	
7.50-20	6.50	218	935	5165	4130	4985	3740	4640	3480	3560	80.0
8.15-15 (28x9-15)	7.00	207	706	4090	3270	3945	2960	3675	2750	2820	63.0
8.25-12	6.50	206	735	3326	2660	3215	2410	2995	2245	2295	64.6
8.25-15	6.50	205	847	4940	3950	4765	3575	4440	3330	3045	86.8
8.25-20	6.50	218	902	5425	4340	5420	3930	4880	3735	3475	115.0
9.00-16	6.50	218	884	5135	4110	4965	3725	4625	3470	3560	103.0
9.00-20	6.50	238	1038	6450	5160	6235	4675	5805	4355	4450	123.0
	7.00	238	1038	6450	5160	6235	4675	5805	4355	4450	
10.00-20	7.50	240	1073	7240	5795	6995	5240	6610	4885	4995	186.0
	8.00	240	1073	7240	5795	6995	5240	6610	4885	4995	
11.00-20	8.00	252	1075	7560	6050	7300	5490	6810	5120	5210	186.0
	8.00	290	1146	8800	7000	8500	6925	8000	6450	6595	
12.00-20	8.50	290	1146	8800	7000	8500	6925	8000	6450	6595	225.0
	200/50-10	6.50	198	458	2370	1900	2290	1720	2135	1605	
250-15	7.00	220	735	4366	3400	4220	3160	3930	2955	3010	66.0
	7.50	226	735	4366	3400	4220	3160	3930	2955	3010	
300-15	8.00	258	838	5990	4700	5780	4335	5380	4037	4130	99.0
15x41/2-8	3.25	106	380	905	725	675	855	805	605	625	9.6
	3.00	106	380	905	725	675	805	605	605	625	
16x6-8	4.33	156	418	1500	1200	1445	1085	1345	1010	1035	14.4
18x7-8	4.33	154	457	2350	1880	2265	1700	2110	1585	1620	20.0
21x8-9	6.00	189	535	2810	2250	2715	2035	2530	1895	1940	33.4
23x9-10	6.50	230	597	4005	3205	3845	2885	3605	2705	2765	46.4
23x10-12	8.00	237	595	3980	3420	3820	3210	3586	3010	2980	50.0
27x10-12	8.00	235	683	4465	3570	4315	3235	4020	3015	3080	67.4
28x12-15	9.75	300	706	5735	4590	5540	4165	5170	3890	3955	80.0
32x12-15	9.75	301	823	7120	6700	8060	6170	7410	5420	4910	90.0

PNSH05

- Applications: lifter or forklift in tough working conditions.
- Super strong pneumatic solid tire improving load capacity and resistance to puncture, extend service life.
- Special colloidal anti-static formula to do the effective elimination of static accumulation, improving the safety of the workplace and personnel.

Size	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity/Balance Forklift (kg)						Other Forklifts		Weight kg
				10km/h		16km/h		26km/h		(kg)		
				Drive	Steer	Drive	Steer	Drive	Steer			
											16km/h	
21x8-9	6.00	184	507	2810	2250	2715	2035	2530	1895	1940	33.4	
23x9-10	6.50	193	575	4005	3205	3845	2885	3605	2705	2765	46.4	
27x10-12	8.00	235	655	4465	3570	4315	3235	4020	3015	3080	67.4	

PNST6-W/PNST6

- Applications: lifter or forklift in tough working conditions.
- Super strong pneumatic solid tire improving load capacity and resistance to puncture, extend service life.
- Special colloidal anti-static formula to do the effective elimination of static accumulation, improving the safety of the workplace and personnel.
- PNSH01-W tires with light-colored rubber formula to eliminate the marking issue on the ground to avoid polluting the operating environment.

Size	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity/Balance Forklift (kg)						Other Forklifts (kg)	Weight kg
				10km/h		16km/h		26km/h			
				Drive	Steer	Drive	Steer	Drive	Steer	16km/h	
5.00-8	3.00	126	469	1210	970	1175	880	1095	820	840	18.0
6.00-9	4.00	140	545	1920	1535	1855	1390	1730	1295	1325	27.8
6.50-10	5.00	157	597	2840	2110	2545	1910	2370	1780	1820	36.6
7.00-9	5.00	170	578	2370	2015	2805	1925	2370	1750	1785	32.2
7.00-12	5.00	168	683	3015	2410	2910	2185	2710	2035	2075	45.0
8.15-15 (28x9-15)	7.00	207	706	4090	3270	3945	2960	3675	2755	2820	63.0
8.25-12	6.50	206	735	3326	2660	3215	2410	2995	2245	2295	64.6
8.25-15	6.50	205	847	4940	3950	4765	3575	4440	3330	3045	86.8
250-15	7.00	220	735	4366	3400	4220	3160	3930	2955	3010	66.0
	7.50	226	735	4366	3400	4220	3160	3930	2955	3010	
300-15	8.00	263	838	5990	4700	5780	4335	5380	4037	4130	99.0
18x7-8	4.33	154	457	2350	1880	2265	1700	2110	1585	1620	20.8
15x4.5-8	3.00	106	380	905	725	675	805	605	605	625	9.6

PNSKS

- Applications: skid steer, lifter or forklift in tough working conditions.
- Solid skid steer tire with special design to eliminate the shock effect and reduce the wear and tear of the vehicle.
- Special casing design to reduce tire weights and save power.
- Special colloidal anti-static formula to do the effective elimination of static accumulation, improving the safety of the workplace and personnel.

Size with Rim	Size without Rim	Raplacing Size	Standard Rim	Section Width mm	Overall Diameter mm	Load @10km/h Kg	Weight Kg
31"x10"	31x10-20	10-16.5	7.50-20	235	740	3415	100.2
33"x11"	33x12-20	12-16.5	7.50-20	276	838	4075	125.0
36"x11"	36x14-20	14-17.5	7.50-20	276	914	5650	178.0
40"x13"	40x15-20	15-19.5	7.50-20	336	1016	7545	275.0
38"x13"	16/70-20	13.00		330	950	6320	208.0